ELCO Lighting

Project Name:

Fixture Type:

Date:

KOTO™ LED MODULE WITH 5-CCT SWITCH

Module · Round · 1 1/2″

Works with 2″, 3″, 4″ & 6″ Recessed Housings and Koto™ Trims



FEATURES

- 5-CCT Switch allows to choose between 2700K, 3000K, 3500K, 4000K or 5000K
- Integrated 120V dimmable driver Triac/ELV
- 90+ CRI color rendering
- Works in 2″, 3″, 4″ & 6″ ELCO Housings with Koto™ twist-on trims
- Energy Star Certified. Title 24 JA8-2025-E Compliant
- Standard 38° Lens installed, 25° and 60° lenses included; modules ordered with a beam suffix (-S 18°, -N 25°, -W 60°, -E 90°) come with that lens only - Optional Lens: 18° (EP731C), 90° (EP739C)
- Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47), Clear Lens (L48), Frosted Lens (L49), White Koto Snoot (L50W). Black Koto Snoot (L50B), Color Shifter (L51), Blue Lens (L52), Pink Lens (L53), Single Asymmetric Lens (L54), Double Asymmetric Lens (L55)
- Covered by U.S. PATENTS and Patents Pending

Please note this will not replace static color temperature Koto modules.

DIMENSIONS



SPECIFICATIONS

Wattage	10.5 · 12.5 W
Lumens	825 · 1000 lm
Voltage	120V
Color temp.	2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	38° · 18° · 25° · 60° · 90°
CRI	95+
Aperture	1 1/2"
Shape	Round

Item page
elcolighting.com/items/koto-led-module-5-cct-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

2″ Standard Koto™ · 3″ Standard Koto™ · 4″ Standard Koto™ · 6″ Standard Koto™ · Standard Koto™ Multiples · 5″ Standard Koto™ · Koto™ Downsizer Ring · 4″ Koto™ Sloped Ceiling

↓ Dimmer compatibility list
elcolighting.com · Dimmer_Koto_Standard_LED_Module

© ELCO Lighting 2026. All rights reserved • Rev. 25 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **Koto™ LED Module with 5-CCT Switch** item number (Select one) Example: **ELK08CT5** Your item number:

ITEM	LUMENS	CCT	BEAM ANGLE
ELK	**08** 825 lm (10.5W) **10** 1000 lm (12.5W)	**CT5** 2700K-5000K	38°[1] **-S** 18° **-N** 25° **-W** 60° **-E** 90°[2]

No separate code: Lumens: 825 lm, 1000 lm

[1] 38° lens installed. Includes 25° and 60° lens with module. [2] 90° Frosted Reflector

TECHNICAL DETAILS

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

Installation: Twist-on design for toolless trim installation, for use with Koto™ trims only. Can be used in 2", 3", 4" & 6" housings with quick connect base.

Electrical: 120V Input Module. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens: Up to 1000 lm/5-CCT Switch

LED Technology: Color Rendering Index of 90+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Thermal management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 5%. For full list of dimmers, refer to the Dimmer Compatibility List. Dims smoothly with no hot spots or flickering.

Listings: UL Listed (US and Canada) for Damp Locations. UL Listed (US and Canada) for Wet Location with Wet location trims. RoHS Compliant. Energy Star Certified. Title 24 JA8-2025-E Compliant

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 25 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.