ELCO Lighting

Project Name:

Fixture Type:

Date:

TROGON™ LED BRICK LIGHT WITH OPEN FACEPLATE

Fixture · Rectangular · 3 finishes



ELCO's Trogon Collection consists of diecast wet location LED Brick Lights which are offered in 5.4W or 12W, 3000K, 120V with an Angled Louver, Open Frame Lens or Grill Faceplate in a sharp White, Black or Bronze powder coated finish.

FEATURES

- Diecast aluminum housing and faceplate.
- Integrated LED board and driver.
- Diffused glass lens behind faceplate.
- Wet Location listed for indoor or outdoor use.
- UL Listed (US and Canada) for poured concrete.
- UL Listed (US and Canada) for direct contact with insulation (type IC).
- Housing equipped with (2) side brackets and (2) ½" knockouts for easy wiring.
- Life span of 35,000 hours L70.

DIMENSIONS



SPECIFICATIONS

Wattage	5.4W
Lumens	340 lm
Voltage	120V
Color temp.	3000K
Lamp type	LED
CRI	90+
Shape	Rectangular

ITEM NUMBERS

ITEM NUMBER	LAMP TYPE	LUMENS	WATTS	VOLTAGE	CCT	FINISH
ELST83B	LED	340 lm	5.4W	120V	3000K	Black
ELST83BZ	LED	340 lm	5.4W	120V	3000K	Bronze
ELST83W	LED	340 lm	5.4W	120V	3000K	White

FINISHES


Black


Bronze


White

Item page
elcolighting.com/items/led-brick-light-open-faceplate
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

Trogon Collection™

TECHNICAL DETAILS

Optics: Open face with frosted glass lens to diffuse light and illuminate walkway .

Construction: Diecast Faceplate with smooth powder coat finish. LED board and driver integrated in housing. Tamper-proof screws for mounting faceplate to box. Heavy duty aluminum housing.

Installation: Suitable for poured concrete and other wall and brick installation types. Housing equipped with two side brackets.

Electrical:

- Housing with 1/2” conduit knockout on each side suitable for thru-wiring.
- Ambient operating temperature -23°F (-5°C) to 113°F (45°C).

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

•Driver input of 120V 50/60Hz connects directly to line voltage power.

LED Technology:

• 90+ CRI color rendering.
• Lumen Maintenance of 35,000 hours L70 Life.
• LED Array.

Listings: cUL and cULus Listed for Wet Location.
IC rated for direct contact with insulation.
Listed for Poured Concrete.

Warranty: ELCO Products are built to last. 5-year Limited warranty

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.