ELCO Lighting

Project Name:

Fixture Type:

Date:

LED GORDIAN™ TRACK FIXTURE

Track Head · 2 finishes

All track fixtures have adjustable adapters to be used with 120V Single or Two Circuit Track



FEATURES

- Solid diecast aluminum fixture
- Integrated driver
- 180° tilt, 358° rotation
- 50,000 hours life-span
- 38° Beam Angle Standard
- CCT Switch available in select fixtures
- Optional lenses: EP719C (15°) or EP720C (24°) available
- This track head comes standard as H Style. J (Juno) and L (Lightolier) styles are available: For J style please order PJTHI (W/B) with the track head. For L style please order PLTHI (W/B) with the track head. Note these must be factory installed.

DIMENSIONS



ET618**D



ET619**D



ET620**D



ET621**D

SPECIFICATIONS

Wattage	10 · 20 · 30 · 40 W
Lumens	750 lm · 1150 lm · 2100 lm - 2250 lm · 2900 lm - 3150 lm
Voltage	120V
Color temp.	3000K · 3000K-4000K · 2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	38°

FINISHES



White



Black

Item page
elcolighting.com/items/led-gordian-track-fixture
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

LED Integrated Track Fixtures

⬇ Dimmer compatibility list

elcolighting.com · ET612-621 Series Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 25 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **LED Gordian™ Track Fixture** item number (Select one) Example: **ET618CT5DW** Your item number:

ITEM	LUMENS	CCT	DIMMING	FINISH
ET	**618** 750 lm **619** 1150 lm **620** 2100 lm - 2250 lm **621** 2900 lm - 3150 lm	**30** 3000K **CT3** 3000K-4000K **CT5** 2700K-5000K	**D** Triac/ELV	**W** White **B** Black

No separate code: Lumens: 2200 lm, 3050 lm

TECHNICAL DETAILS

Construction: Full diecast construction for heat management. Powder coat architectural white and architectural black matte finishes.

Adjustability: Track head is adjustable 180° tilt with 358° rotation.

Optics: Lens provides smooth lumen output at standard 38°. Optional lenses for Gordian™ (ET61830D & ET61930D): EP719C (15°) or EP720C (24°) available. Optional Lenses for Gordian™ (ET620D): EP722C (15°) or EP723C (24°) available. Optical Lenses inlcuded Gordian™ (ET621CT3D): 15° or 24° available

Installation: Installs into H-Style track from ELCO or others. Compatible with Single and two circuit track. Can be special ordered as J-Style (requires PJTLO W/B) or L-Style (requires PLTLO W/B).

LED Technology: Color Rendering Index of 90+ CRI. Efficacy of over 81 lumens per watt. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Instant On to Full Brightness technology. Chip on Board LED design results in a smooth lumen output with no LED pixelation

Dimmability: Triac and ELV dimmable down to 10%. For full list of dimmers refer to the Dimmer Compatibility List

Electrical: Driver is rated for 120V input. High Efficiency driver with a power factor > 0.9

Listings: ETL Listed. RoHS Compliant

Warranty: ELCO Products are built to last. 5-year Limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 25 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.