ELCO Lighting

Project Name:

Fixture Type:

Date:

LED PACKER™ TRACK FIXTURE WITH 5-CCT & 3-WATTAGE SWITCH

Track Head · 2 finishes

All track fixtures have adjustable adapters to be used with 120V Single or Two Circuit Track



FEATURES

- Diecast aluminum fixture with integrated driver
- 90° vertical adjustment, 358° rotation
- Manual 5-CCT and 3-Wattage Switch available in fixture
- Standard 36° beam angle. Includes field changeable 24° lens (for ET830/ET831) and 60° lens (for ET832/ET833)
- Use with ELCO 120V Single or Two Circuit Track
- 50,000 hours life-span
- This track head comes standard as H Style. J (Juno) and L (Lightolier) styles are available: For J style please order PJTHI (W/B) with the track head. For L style please order PLTHI (W/B) with the track head. Note these must be factory installed

DIMENSIONS



ET833CT5



ET833CT5



ET833CT5



ET833CT5

SPECIFICATIONS

Wattage	7W, 10W, 14W · 10W, 15W, 20W · 20W, 24W, 28W · 24W, 30W, 36W
Lumens	650/950/1250 lm · 925/1400/1750 lm · 1750/2050/2375 lm · 2075/2675/3075 lm
Voltage	120V
Color temp.	2700K-5000K
Lamp type	LED
Beam angle	36°

FINISHES


White


Black

Item page
elcolighting.com/items/led-packer-track-fixture-5-cct-3-wattage-switch
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

LED Integrated Track Fixtures

↓ Dimmer compatibility list

elcolighting.com · ET830CT5-ET833CT5 Dimming Chart

© ELCO Lighting 2026. All rights reserved • Rev. 24 Jun 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **LED Packer™ Track Fixture with 5-CCT & 3-Wattage Switch** item number (Select one) Example: **ET830CT5W** Your item number:

ITEM	LUMENS	CCT	FINISH
ET	**830** 650/950/1250 lm **831** 925/1400/1750 lm **832** 1750/2050/2375 lm **833** 2075/2675/3075 lm	**CT5** 2700K-5000K	**W** White **B** Black

No separate code: Lumens: 650, 950, 1250, 925, 1400, 1750, 1750, 2050, 2375, 2075, 2675, 3075

TECHNICAL DETAILS

Construction: Full diecast construction for heat management. Powder coat white and black matte finishes.

Adjustability: Track head is adjustable 90° vertically with 358° rotation.

Optics: Lens provides smooth lumen output at standard 36°. Field changeable 24° lens (for ET830/ET831) and 60° lens (for ET832/ET833) included.

Installation: Installs into H-Style track from ELCO or others. Compatible with Single and two circuit track. Can be special ordered as J-Style (requires PJTLO W/B) or L-Style (requires PLTLO W/B).

LED Technology: Color Rendering Index of 93+ CRI. Lumen maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Instant On to Full Brightness technology. Chip on Board LED design results in a smooth lumen output with no LED pixelation

Dimmability: Triac/ELV dimmable down to 10%. For full list of dimmers refer to the Dimmer Compatibility List

Electrical: Driver is rated for 120V input. High Efficiency driver with a power factor > 0.9

Delivered Lumens: ET830CT5 @3500 650/950/1250 lm @4000 675/975/1275 lm, **ET831CT5** @3500 925/1400/1750 lm @4000 950/1450/1800 lm, **ET832CT5** @3500 1750/2050/2375 lm @4000 1800/2125/2450 lm, **ET833CT5** @3500 2075/2625/3075 lm @4000 2150/2700/3175 lm

Listings: RoHS Compliant. ETL Listed

Warranty: ELCO Products are built to last. 5-year Limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 24 Jun 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.