ELCO Lighting

Project Name:

Fixture Type:

Date:

LED STEIN™ TRACK FIXTURE

Track Head · 2 finishes

All track fixtures have adjustable adapters to be used with 120V Single or Two Circuit Track.



FEATURES

- Diecast adjustable track fixture.
- Integrated driver.
- 50,000 hours life-span.
- **ET616 & ET617 Series:** Includes 38° standard beam angle (installed), and field changeable 25° & 15° lenses in the box
- **ET843 Series:** Includes 38° standard beam angle (installed) and field changeable 60° lens in the box
- 180° vertical adjustment, 358° rotation.
- Use with ELCO 120V Single or Two Circuit Track.
- High efficacy COB LED.
- This track head comes standard as H Style. J (Juno) and L (Lightolier) styles are available: For J style please order PJTHI (W/B) with the track head. For L style please order PLTHI (W/B) with the track head. Note these must be factory installed.
- Optional: Snoot available. For use with Black finish track heads only.

DIMENSIONS



ET843



ET843



ET843

SPECIFICATIONS

Wattage	10W · 20W · 20/30/36
Lumens	800 lm · 1500 lm · 2050/2600/3050 · 2600 lm
Voltage	120V
Color temp.	2700K · 2700K-5000K
Dimming	Triac/ELV
Lamp type	LED
Beam angle	38°
Accessory option	Snoot · Louver

FINISHES


White


Black

Item page
elcolighting.com/items/led-stein-track-fixture
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

LED Integrated Track Fixtures

↓ Dimmer compatibility list

elcolighting.com · ET612-621 Series Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 10 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **LED Stein™ Track Fixture** item number (Select one) Example: **ET616CT5DW** Your item number:

ITEM	LUMENS	CCT	DIMMING	FINISH
ET	**616** 800 lm **617** 1500 lm **843** 2600 lm 2050/2600/3050	**-27** 2700K **CT5** 2700K-5000K	**D** Triac/ELV	**W** White **B** Black

TECHNICAL DETAILS

Construction: Full diecast construction for heat management. Powder coat architectural white and architectural black matte finishes.

Adjustability: Track head is adjustable 180° vertically with 358° rotation.

Optics: Lens provides smooth lumen output at standard 38° (installed), 25° and 15° lenses in the box (for ET616 & ET617 Series), and 60° lens in the box (for ET843 Series)

Installation: Installs into H-Style track from ELCO or others. Compatible with Single and two circuit track. Can be special ordered as J-Style (requires PJTLO W/B) or L-Style (requires PLTLO W/B).

LED Technology: Color Rendering Index of 93+ CRI. Efficacy of over 83 lumens per watt. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Instant On to Full Brightness technology. Chip on Board LED design results in a smooth lumen output with no LED pixelation

Dimmability: Triac and ELV dimmable down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.

Electrical: Driver is rated for 120V input. High Efficiency driver with a power factor > 0.9

Listings: ETL Listed. RoHS Compliant.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 10 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.