ELCO Lighting

Project Name:

Fixture Type:

Date:

LED TRANSOM™ TRACK FIXTURE

Track Head · 2 finishes

All track fixtures have adjustable adapters to be used with 120V Single or Two Circuit Track



FEATURES

- Diecast adjustable track fixture
- Integrated Driver
- 180° tilt, 358° rotation
- 38° Beam Angle Standard
- Optional lenses for Transom™ (ET612D): EP719C (15°) or EP720C (24°) available. Optional Lenses Transom™ (ET613D): EP722C (15°) or EP723C (24°) available.
- This track head comes standard as H Style. ET613CT5 is not compatible with J or L style. J (Juno) and L (Lightolier) styles are available: For J style please order PJTHI (W/B) with the track head. For L style please order PLTHI (W/B) with the track head. Note these must be factory installed.

DIMENSIONS



ET612D



ET613D

SPECIFICATIONS

Wattage	10 · 17 · 18 W
Lumens	800 · 1500 lm
Voltage	120V
Color temp.	3000K · 4000K · 2700K-5000K
Dimming	Triac/ELV
Beam angle	38°
CRI	90+

FINISHES



White



Black

Item page
elcolighting.com/items/led-transom-track-fixture-1
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

LED Integrated Track Fixtures

↓ Dimmer compatibility list

elcolighting.com · ET612-621 Series Dimmer List

© ELCO Lighting 2026. All rights reserved • Rev. 25 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **LED Transom™ Track Fixture** item number (Select one) Example: **ET612DW** Your item number:

ITEM	LUMENS	CCT	DIMMING	FINISH
ET	**612** 800 lm **613** 1500 lm	3000K **-40** 4000K **CT5** 2700K-5000K[1]	**D** Triac/ELV	**W** White **B** Black

[1] Not compatible with J or L style

TECHNICAL DETAILS

Construction: Full diecast construction for heat management. Powder coat architectural white and architectural black matte finishes.

Adjustability: Track head is adjustable 180° vertically with 358° rotation.

Optics: Lens provides smooth lumen output at standard 38°. Lens available as accessory for ET612D with 15° (EP719C) or 24° (EP720C). Lens available as accessory For ET613D with 15° (EP722C) or 24° (EP723C).

Installation: Installs into H-Style track from ELCO or others. Compatible with Single and two circuit track. Can be special ordered as J-Style (requires PJTLO W/B) or L-Style (requires PLTLO W/B).

LED Technology:

- Color Rendering Index of 93+ CRI
- Efficacy of over 88 lumens per watt
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results
- Instant On to Full Brightness technology
- Chip on Board LED design results in a smooth lumen output with no LED pixelation

Dimmability:

- Triac and ELV dimmable down to 10%
- For full list of dimmers refer to the Dimmer Compatibility List

Electrical:

- Driver is rated for 120V input
- High Efficiency driver with a power factor > 0.9

Listings:

- ETL Listed
- RoHS Compliant

Warranty: ELCO Products are built to last. 5-year Limited warranty.

© ELCO Lighting 2026. All rights reserved • Rev. 25 Sep 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.