ELCO Lighting

Project Name:

Fixture Type:

Date:

OAK™ ARCHITECTURAL IC REMODEL POWER PACK

Downlight

IC Rated Remodel Power Pack to be used with Oak™ Architectural LED Light Engines only.



FEATURES

- To be used with Oak™ Architectural Light Engines only.
- Fits through 2″ hole.
- IC Rated for direct contact with insulation.
- 8W driver.
- Driver specified for 120V (Triac/ELV) or 120/277V (0-10V/Triac/ELV).
- Damp Location Listed, Wet Location with Wet Location Oak™ Light Engines.
- JA8-2025-E, UL Listed.

DIMENSIONS



SPECIFICATIONS

Wattage	8W
Voltage	120V · 120-277V
Dimming	Triac/ELV · 0-10V/Triac/ELV

Item page
elcolighting.com/items/oak-architectural-ic-remodel-power-pack
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

Architectural Oak™

↓ Dimmer compatibility list

elcolighting.com · Architectural Oak System Dimmer List

PRODUCT NUMBER BUILDER

Specify **Oak™ Architectural IC Remodel Power Pack** item number (Select one) Example: **E1RLA08IC** Your item number:

ITEM	DIMMING
E1RLA08	**IC** Triac/ELV **ICDX** 0-10V/Triac/ELV

TECHNICAL DETAILS

Construction: IC rated for direct contact with insulation. For use in IC and Non-IC conditions.

Installation: Can be used in remodel applications without any additional frame. Can be used in new construction applications with E1LF1 & E1LF2 frame series.

Electrical: Driver is rated for 120V or 120/277V input. High Efficiency driver with a power factor > 0.95.

Dimmability: Option Triac/ELV dimming or 0-10V/Triac/ELV dimming can be specified.

Listings: UL Listed (US and Canada). UL Listed for Damp Location and for Wet Location with WET location Light Engines.

© ELCO Lighting 2026. All rights reserved • Rev. 19 Oct 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.