ELCO Lighting

Project Name:

Fixture Type:

Date:

IBIS™ ROUND LED STEP LIGHT WITH OPEN FACEPLATE

Fixture · Round · 5 finishes



ELCO's Ibis Collection consists of diecast wet location mini LED Step Lights which are offered in 2W or 3W, 3000K or 4000K, 120V or 12V AC/DC in round or rectangle with an Angled Louver, Open Frame Lens or Scoop Faceplate.

FEATURES

- Single Piece Diecast aluminum faceplate.
- Powder Coated Faceplate.
- Integrated LED board and driver.
- Diffused lens behind faceplate.
- Wet Location listed for indoor or outdoor use.
- Mounts in a round junction box.
- 1 9/16″ Depth
- Life span of 50,000 hours L70.
- Input Volt: 12V or 120V. (12V units work with 12V AC or 12V DC supply)
- Rated: IP67.

DIMENSIONS





SPECIFICATIONS

Wattage	3W
Voltage	12V · 120V
Color temp.	3000K · 4000K
Lamp type	LED
CRI	90+
Shape	Round

FINISHES


White


Black


Nickel


Copper


Bronze

Item page
elcolighting.com/items/round-mini-led-step-light-open-faceplate
Every item number, IES files, downloads and the latest revision.

PART OF THESE FAMILIES

Ibis Collection™

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.

PRODUCT NUMBER BUILDER

Specify **Ibis™ Round LED Step Light with Open Faceplate** item number (Select one) Example: **ELST8430B** Your item number:

ITEM	VOLTAGE	CCT	FINISH
ELST8	**4** 12V **6** 120V	**30** 3000K **40** 4000K	**W** White **B** Black **N** Nickel **CP** Copper **BZ** Bronze

TECHNICAL DETAILS

Optics: Frosted lens diffuses light and illuminates walkway.

Construction: Diecast Faceplate with smooth powder coat finish. LED board and driver integrated in housing. Security screws for mounting faceplate to box included.

Installation: Easily installs into a round junction box.

Electrical:

- Ambient operating temperature -23°F (-5°C) to 113°F (45°C).
- 120V ELST86: Driver input of 120V 50/60Hz connects directly to line voltage power.
- 12V ELST84: Input of 12V requires an external transformer. (12V units work with 12V AC or 12V DC supply)

LED Technology:

- 90+ CRI color rendering.
- Lumen Maintenance of 50,000 hours L70 Life.
- LED Array.

Listings: cETLus listed for Wet Location.

Warranty: ELCO Products are built to last. 5-year Limited warranty

© ELCO Lighting 2026. All rights reserved • Rev. 01 Nov 2026 • ELCO Lighting reserves the right to make specification and design changes without notice.