

Project name:

Fixture type:

Date:

# 0-10V Koto<sup>™</sup> LED Module

Works with 2", 3", 4", and 6" ELCO 0-10V Recessed Housings and Koto™ Trims



#### Features

- Integrated 120-277V (50/60Hz), 0-10V/Triac/ELV dimmable driver
- Excellent color rendering 95+ CRI
- Sunset Module ELK10DXSD starts from 3000K and dims to 1800K
- Works in 2<sup>"</sup>, 3<sup>"</sup>, 4<sup>"</sup>, and 6<sup>"</sup> ELCO 0-10V Housings with Koto™ twist-on trims
- Energy Star Certified
- Title 24 JA8-2019 Compliant
- Standard 38° Lens installed, 25° and 60° lens included with each module - Optional Lens: 18° (EP731C), 90° (EP739C)
- Optional: Louver (<u>L45</u>), Linear Lens (<u>L46</u>), Spread Lens (<u>L47</u>), Clear Lens (<u>L48</u>), Frosted Lens (<u>L49</u>), Snoot (<u>L50</u>), Color Shifter (<u>L51</u>), Blue Lens (<u>L52</u>), Pink Lens (<u>L53</u>), Single Asymmetric Lens (<u>L54</u>), Double Asymmetric Lens (<u>L55</u>)
- Covered by U.S. PATENTS and Patents Pending

#### **Technical Details**

**Optics**: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Construction**: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

Installation: Twist-on design for toolless trim installation, for use with Koto<sup>™</sup> trims only. Can be use in 2", 3", 4" and 6" ELCO 0-10V Recessed Housings.

**Electrical:** Module connects to 120-277V input power. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

#### Delivered Lumens: 1000 lm (11.8W)

**LED Technology:** Extremely accurate Color Rendering Index of 95+. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.


**Sunset:** Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: Works with 120-277V input, 0-10V/Triac/ELV type dimmers. Dims down to 5%. For full list of

#### Specifications

Wattage	11.8W		
Lumens	1000 lm		
Voltage	120-277V		
Color Temp.	2700K - SunsetK		
Dimmable	0-10V/Triac/ELV		
Lamp Type	LED		
Beam Angle	38° - 90°		
CRI	95		
Wet Location	cUL Listed w/Wet Location Trim		
Damp Location CUL Listed			

#### Dimensions



dimmers, refer to the Dimmer Compatibility List. Industry leading dimming that dims smoothly with no hot spots or flickering. Listings: cUL Listed for Damp Locations. cUL Listed for Wet Location with Wet location trims. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2019 standards. Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

#### Product Number Builder Example: ELK10DX27

DX Koto <sup>™</sup> LED Module	Lumens	Voltage	Color Temp.	Beam Angle
ELK				
	10 1000 lm (11.8W)	<b>DX</b> 120-277V	<b>27</b> 2700K	38° <sup>2</sup>
			<b>30</b> 3000K	<b>-S</b> 18°
			<b>35</b> 3500K	<b>-N</b> 25°
			<b>40</b> 4000K	<b>-W</b> 60°
			SD Sunset <sup>1</sup>	<b>-E</b> 90° <sup>3</sup>
1				

<sup>1</sup> Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

 $^{2}$  38° lens installed. Includes 25° and 60° lens with module.

<sup>3</sup> 90° Frosted Reflector



For use with **0-10V Koto™ LED Module** 

### 2″ Koto™ Dedicated LED ICA Housings



2″ ICA Maximum Adjustability Housing New Construction

CAT NO. SPECIFICATIONS EL276ICDXA Maximum Adjustability

#### 2" Pex™ Twist-On Trims




Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B\* - All Black (For ELK2872, ELK2888, ELK2588, & ELK215)

For use with  $\textbf{0-10V}\ \textbf{Koto}^{\text{\tiny TM}}\ \textbf{LED}\ \textbf{Module}$ 




### 3″ Koto™ Dedicated LED ICA Housings



\*Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring

For use with 0-10V Koto<sup>™</sup> LED Module





Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B\* - All Black (For ELK315, ELK370, & ELK381)

For use with **0-10V Koto<sup>™</sup> LED Module** 



### **4**″ Koto<sup>™</sup> Dedicated LED ICA Housings



4" ICA Maximum Adjustability Housing New Construction

EL485ICDXA Maximum Adjustability

SPECIFICATIONS



4" ICA Housing New Construction


SPECIFICATIONS

EL490ICDXA 14W, 120/277V EL490ICDXA-EM5 Emergency

CAT NO.

CAT NO.

L490ICDXA-EM5 Emergency Battery Back-up (90 minutes)



.....

Recommended to be used with Maximum

Adjustability Housing

4" R-60 Spray Foam Insulation Housing New Construction

CAT NO.	SPECIFICATIONS
EL490AJICDXA	Maximum Adj. for use in R60 or Chicago plenum applications



4" ICA Housing Remodel

SPECIFICATIONS

EL490RICDXA 14W, 120V

CAT NO.

CAT NO.


#### **4″** Pex™ Twist-On Trims



2-Hour Fire Rated 4" ICA Housing New Construction

SPECIFICATIONS


EL48FICDXA 7 1/2" Height, Sound Rated



Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B\* - All Black (For ELK4188, ELK4128, & ELK4284)

For use with 0-10V Koto<sup>™</sup> LED Module

### EL ELCO Lighting




Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B\* - All Black, (For ELK408, ELK415, ELK434, ELK445, ELK459)

For use with **0-10V Koto™ LED Module** 

### **4″** Flexa™ Twist-On Trims






\*Finishes: W - All White, WW - All White, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring, BB - All Black, BZ - All Bronze, CC - All Chrome, BZBZ - All Bronze, BW - Black Reflector w/White Ring, CW - Chrome Reflector w/White Ring, CN - Chrome Reflector w/Nickel Ring, HW - Haze Reflector w/White Ring

**EL ELCO** Lighting

For use with 0-10V Koto<sup>™</sup> LED Module

### 6" Koto™ Dedicated LED ICA Housings



Finishes: (W)

ELK6427 Finishes: (W, B, H)

ELK6829 Finishes: (W, BB, H)

\*Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring

For use with 0-10V Koto<sup>™</sup> LED Module




### 6" Flexa<sup>™</sup> Twist-On Trims





#### 6" Round Reflector ELK610 Finishes: (WW, BB, BZBZ, CC, BW, CW, HW)





Finishes: (WW, BB, BZBZ, BW)

### 6" Unique™ Twist-On Trims



6" Round Reflector ELK6710

Finishes: (W, B, BZ)



6" Round Baffle ELK6713 Finishes: (W, BZ)



6" Round Wall Wash ELK6715 Finishes: (W, BZ)

Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B\* - All Black (For ELK6710, ELK6713, ELK671