

Project name:
Fixture type:
Date:

0-10V Koto™ LED Module

Works with 2", 3", 4", and 6" ELCO 0-10V Recessed Housings and Koto™ Trims




Features

- Integrated 120-277V (50/60Hz), 0-10V/Triac/ELV dimmable driver
- Excellent color rendering 95+ CRI
- Sunset Module ELK10DXSD starts from 3000K and dims to 1800K
- Works in 2", 3", 4", and 6" ELCO 0-10V Housings with Koto™ twist-on trims
- Energy Star Certified
- Title 24 JA8-2019 Compliant
- Standard 38° Lens installed, 25° and 60° lens included with each module - Optional Lens: 18° (EP731C), 90° (EP739C)
- Optional: Louver (<u>L45</u>), Linear Lens (<u>L46</u>), Spread Lens (<u>L47</u>), Clear Lens (<u>L48</u>), Frosted Lens (<u>L49</u>), Snoot (<u>L50</u>), Color Shifter (<u>L51</u>), Blue Lens (<u>L52</u>), Pink Lens (<u>L53</u>), Single Asymmetric Lens (<u>L54</u>), Double Asymmetric Lens (<u>L55</u>)
- Covered by U.S. PATENTS and Patents Pending

Specifications

Wattage	11.8W	
Lumens	1000 lm	
Voltage	120-277V	
Color Temp.	SunsetK	
Dimmable	0-10V/Triac/ELV	
Lamp Type	LED	
Beam Angle	90°	
CRI	95	
Wet Location	cUL Listed w/Wet Location Trim	
Damp Location cUL Listed		

Dimensions



Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

Installation: Twist-on design for toolless trim installation, for use with Koto™ trims only. Can be use in 2", 3", 4" and 6" ELCO 0-10V Recessed Housings.

Electrical: Module connects to 120-277V input power. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

Delivered Lumens: 1000 lm (11.8W)

LED Technology: Extremely accurate Color Rendering Index of 95+. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: Works with 120-277V input, 0-10V/Triac/ELV type dimmers. Dims down to 5%. For full list of

dimmers, refer to the Dimmer Compatibility List. Industry leading dimming that dims smoothly with no hot spots or flickering.

Listings: cUL Listed for Damp Locations. cUL Listed for Wet Location with Wet location trims. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2019 standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Number Builder Example: ELK10DX27

DX Koto™ LED Module	Lumens	Voltage	Color Temp.	Beam Angle
ELK				
	10 1000 lm (11.8W)	DX 120-277V	27 2700K	38° ²
			30 3000K	-S 18°
			35 3500K	-N 25°
			40 4000K	-W 60°
			SD Sunset ¹	-E 90° ³

 $^{^{\}mathrm{1}}$ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

² 38° lens installed. Includes 25° and 60° lens with module.

³ 90° Frosted Reflector



For use with **0-10V Koto[™] LED Module**

2" Koto™ Dedicated LED ICA Housings



2" ICA Maximum Adjustability Housing
New Construction

CAT NO.

SPECIFICATIONS

EL276ICDXA

Maximum Adjustability

2" Pex™ Twist-On Trims



Round Deep Reflector

ELK2818 Finishes: (W, B, H, BB, BZ)



Square Deep Reflector

ELK2518 Finishes: (W, B, BB)



Round Gimbal ELK2888 Finishes: (W, B*, BZ)



Round Adjustable Reflector

ELK2829 Finishes: (W, B, H, BB, BZ)



Square Adjustable Reflector

ELK2529 Finishes: (W, B, BB)



Square Gimbal ELK2588

Finishes: (W, B*, BZ)



Round Adjustable Pinhole

ELK2827 Finishes: (W, B, BB, BZ)



Square Reflector

ELK2541 Finishes: (W, B, BB)



Round Adj. Trimless Reflector

ELK215
Finishes:
(W, B*)



Round Curved Reflector

ELK2872 Finishes: (W, B*)



Square Adjustable Pinhole

ELK2527 Finishes: (W, B, BB)



Trimless Spackle Frame EL2SFR

For use with ELK215

Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B* - All Black (For ELK2872, ELK2888, ELK2588, & ELK215)



For use with **0-10V Koto[™] LED Module**

3" Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated 3" ICA Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL39FICDXA	7 ½" Height - Sound Rated



3" ICA Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL390ICDXA	
EL390ICDXA-EM5	Emergency Battery

Back-up (90 minutes)



3" ICA Maximum Adjustability Housing **New Construction**

CAT NO.	SPECIFICATIONS
EI 386ICDXV	Maximum Adjustability



3" ICA Housing Remodel

CAT NO.	SPECIFICATIONS
EL390RICDXA	

3" Pex™ Twist-On Trims









Round Adj. Wall Wash

ELK3622 Finishes: (W)



Round Adjustable Baffle ELK3693 Finishes:

(W)



Round Adjustable Gimbal

ELK3629 Finishes: (W, BB, BZ, B, C, H)



Round Regressed Eyeball

ELK3653 Finishes: (W, BB, B)



Square Deep Reflector

ELK3318 Finishes: (W, BB, BZ, B, C, H)



Round Adjustable Pinhole

ELK3627 Finishes: (B, BB, BZ, B, H)



Round Curved Reflector

ELK3672 Finishes: (W, B)



Square Adjustable Reflector

ELK3329 Finishes: (W, BB, BZ, B, C, H)





Round Adj. Slot Aperture

ELK3620 Finishes: (W)



Round Directional Gimbal

ELK3679 Finishes: (W, BB, B, H)



Square Adj. Wall Wash ELK3322

Finishes: (W)

*Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring



For use with **0-10V Koto™ LED Module**

3" Pex™ Twist-On Trims





Square Adjustable Pinhole ELK3327

Finishes: (W, BB, BZ, B, H)



Square Reflector

ELK3341 Finishes: (W, BB, BZ, B)



Square Adjustable Baffle

ELK3393 Finishes: (W)

3" Pex™ Flush Mount Trim Adaptors



Round Flush Mount Trim Adaptor

FI 3FMR

Compatible 3" Pex™ Round trims: ELK3618, ELK3629, ELK3627, ELK3693, ELK3620, ELK3622 Series



Square Flush Mount Trim Adaptor

EL3FMS

Compatible 3" Pex™ Square trims: ELK3318, ELK3329, ELK3322, ELK3327, ELK3341, ELK3393 Series

3" Pex™ Trimless



used with Maximum Adjustability Housing



Round Trimless Reflector

ELK308 Finishes: (W, B, H)



Square Trimless

Reflector **ELK370** Finishes: (W, B, H)



Round Adjustable **Trimless Reflector**

ELK315 Finishes: (W, B, H)



Square Adjustable **Trimless Reflector ELK381**

Finishes: (W, B, H)



Round Trimless Spackle Frame EL3SFR

For use with ELK315





Square Trimless Spackle Frame EL03SFS

For use with ELK370 & ELK381



Round Knife Edge Wood Ceiling Trim w/Mounting Clips

EL3WCR Finishes: (W, B)

Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B* - All Black (For ELK315, ELK370, & ELK381)



For use with **0-10V Koto™ LED Module**

4" Koto™ Dedicated LED ICA Housings



4" ICA Maximum Adjustability Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL485ICDXA	Maximum Adjustability



4" ICA Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL490ICDXA	14W, 120/277V
EL490ICDXA-EM5	Emergency Battery



4" R-60 Spray Foam Insulation Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL490AJICDXA	Maximum Adj. for use in R60 or Chicago plenum applications



4" ICA Housing Remodel

CAT NO.	SPECIFICATIONS	
EL490RICDXA	14W, 120V	



2-Hour Fire Rated 4" ICA Housing **New Construction**

CAI NO.	SPECIFICATIONS
FI 48FICDXA	7 1/2" Height Sound Rated



Pex[™] Twist-On Trims



Reflector ELK4116 Finishes:

(W, H)



Reflector ELK4118 Finishes: (W, BB, BZ, B, C, H)



Réflector ELK4129 Finishes:

(W, BB, BZ, B, C, H)



Adjustable Reflector with Clear Glass

ELK4111 Finishes: (W, BB, BZ, B, C, H)



Adjustable Reflector with Frosted Lens

ELK4112 Finishes: (W, BB, BZ, B, C, H)



Slot Aperture ELK4120 Finishes:

(W)



Adjustable Wall Wash ELK4122 Finishes: (W)



Adjustable Pinhole ELK4127 Finishes:

(W, BB, BZ, B, H)



Adjustable Pinhole with Frosted Glass

ELK4125 Finishes: (W, BB, BZ, B, H)



Slot Aperture

ELK4130 Finishes: (W)



Adjustable Spot ELK4188 Finishes:

(W, B, BZ)



Regressed Eyeball ELK4153 Finishes:

(W, BB, B)



Curved Reflector ELK4172

Finishes:



Directional Gimbal ELK4179 Finishes:

(W, BB, B, H)

Adjustable Baffle

ELK4193 Finishes: (W, BB, B)

(W, B) Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B* - All Black (For ELK4188, ELK4172, & ELK4284)



For use with **0-10V Koto™ LED Module**

4" Pex[™] Twist-On Trims





Shallow Reflector

ELK4216 Finishes: (W, H)



Adjustable Pinhole ELK4227

Finishes: (W, BB, BZ, B, C, H)



Deep Reflector

ELK4218 Finishes: (W, BB, BZ, B, C, H)



Adjustable Reflector

ELK4282 Finishes: (W, BZ)



Adjustable Gimbal

ELK4229 Finishes: (W, BB, BZ, B, C, H)



Adjustable Baffle

ELK4284 Finishes: (W, B, BZ)



Adjustable Slot Rotatable Aperture ELK4220

Finishes: (W)



Adjustable Wall Wash ELK4222

Finishes: (W)



Adj. Phenolic Baffle

ELK4293 Finishes: (W, BB, B)

4" Pex™Flush Mount Trim Adaptors



Round Flush Mount Trim Adaptor

EL4FMR

Compatible 3" Pex™ Round trims: ELK4116, ELK4118, ELK4127, ELK4129, ELK4710, ELK4713, ELK4715 Series



Square Flush Mount Trim Adaptor

EL4FM:

Compatible 3" Pex™ Square trims: ELK4216, ELK4218, ELK4227, ELK4229 Series

4" Pex™ Trimless



Round Trimless Reflector

ELK408 Finishes: (W, B, H, BZ)



Baffle ELK434 Finishes:

(W, B, BZ)



Round Adj. Trimless Reflector

ELK415 Finishes: (W, B, H, BZ)



Square Trimless Reflector

ELK445 Finishes: (W, B, H)



Round Trimless Spackle Frame

EL4SFRFor use with ELK408 & ELK415



Square Trimless Adj. Reflector

ELK459 Finishes: (W, B, H)



used with Maximum Adjustability Housing

Smooth Reflector

ELK430 Finishes: (W, B, BZ)



Square Trimless Spackle Frame

EL4SFS

For use with ELK445 & ELK459

Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B* - All Black (For ELK408, ELK415, ELK434, ELK454), ELK459, ELK459)



For use with **0-10V Koto™ LED Module**

4" Flexa™ Twist-On Trims



Round Reflector

ELK4721 Finishes: (WW, BB, BZBZ, BW, CW, HW)



Round Baffle

ELK4723 Finishes: (WW, BB, BZBZ, BW)



Square Reflector

ELK4741
Finishes:
(WW, BB, BZBZ,
BW, HW)
*Not for Remodel Housing



Square Baffle

ELK4743 Finishes:

(WW, BB, BZBZ, BW)
*Not for Remodel Housing



Square Adj. Reflector

ELK4759 Finishes:

(WW, BB, B, H)

*Not for Remodel Housing

4" Unique™ Twist-On Trims



Round Adjustable Reflector

ELK4710 Finishes: (W, B, BZ)



Round Adj. Deep Baffle

ELK4719 Finishes: (W)



Round Adjustable Baffle

ELK4713 Finishes: (W, BZ)



Square Reflector

ELK4714
Finishes:
(W, B, BZ)
*Not for Remodel Housing



Round Wall Wash

ELK4715 Finishes: (W, BZ)



Square Baffle

ELK4716
Finishes:
(W, BZ)
*Not for Remodel Housing



Round Adj. Deep Reflector

ELK4717 Finishes: (W, BZ)

*Finishes: **W** - All White, **WW** - All White, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring, **BB** - All Black, **BZ** - All Bronze, **CC** - All Chrome, **BZBZ** - All Bronze, **BW** - Black Reflector w/White Ring, **CW** - Chrome Reflector w/White Ring, **CN** - Chrome Reflector w/Nickel Ring, **HW** - Haze Reflector w/White Ring



For use with **0-10V Koto™ LED Module**

6" Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated 6" ICA Housing **New Construction**

CAT NO. SPECIFICATIONS EL76FICDXA 7 ¾" Height



6" Standard ICA Housing **New Construction**


SPECIFICATIONS EL770ICDXA 7 1/2" Height

CAT NO.




6" Standard ICA Housing Remodel

CAT NO. SPECIFICATIONS EL770RICDXA 7 1/2" Height



2-Hour Shallow Fire Rated 6" ICA Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL75FICDXAS	6 3/16" Height



6" Shallow ICA Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL760ICDXA	5 ½" Height



6" Shallow ICA Housing Remodel

CAT NO.	SPECIFICATIONS
EL760RICDXA	5 ½" Height

5" & 6" Pex™ Twist-On Trims



5" Round Reflector

ELK5421 Finishes: (W)



6" Round Adj. Slot Aperture ELK6420W

Finishes: (W)



5" Round Baffle

ELK5493 Finishes: (W)



6" Round Adj. Pinhole Reflector

ELK6427 Finishes: (W, B, H)



6" Round Reflector

ELK6418 Finishes: (W, BB, BZ, H)



6" Square Adj. Reflector

ELK6829 Finishes: (W, BB, H)



6" Round Adj. Reflector

ELK6429 Finishes: (W, BB, BZ, H)

*Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring



For use with **0-10V Koto™ LED Module**

6" Flexa™ Twist-On Trims



6" Round Reflector

ELK610 Finishes: (WW, BB, BZBZ, CC, BW, CW, HW)



6" Round Adjustable Reflector 6" Round Adjustable Baffle

ELK629 Finishes: (WW, BB, BZBZ, BW, CW, HW)



ELK693 Finishes: (WW, BB, BZBZ, BW)

6" Unique™ Twist-On Trims



6" Round Reflector

ELK6710 Finishes: (W, B, BZ)



6" Round Baffle

ELK6713 Finishes: (W, BZ)



6" Round Wall Wash

ELK6715 Finishes: (W, BZ)

Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B* - All Black (For ELK6710, ELK6713, ELK6715)