

1" Square Pull Down Recessed Architectural Oak™ Adjustable

Small aperture downlight delivers up to 900 lumens with 30° adjustability. More than a traditional 50W MR16 halogen lamp. Style options, beam options, and color finish options offer maximum flexibility in design. Drivers and housings are specified separately for maximum flexibility per your project's needs. The patented engine offers auto-release clips that make installation a breeze.



Features

- IC Airtight for use with Direct Contact to insulation
- 30° gimbal adjustability
- Works with compatible ceilings up to 1¼"
- Height allows for use in ceilings with under 2" depth. Ceiling thickness can be reduced from fixture depth.
- Remodel requires no frame. New construction E1ATB08AJIC frame available
- 38° Standard beam with optional 28° and 50°
- Damp Location Rated
- JA8-2022-E, UL Listed, and Energy Star Qualified
- Life Span 50,000 Hours L70

Specifications

| | |
|----------------------|--------|
| Wattage | 8W |
| Lumens | 850 lm |
| Color Temp. | 2700K |
| Lamp Type | LED |
| Beam Angle | 38° |
| CRI | 93+ |
| Damp Location | Listed |

Options



All White



All Black

Technical Details

Optics: PC Lens for even light distribution. Standard 38° lens. Optional 28° (EP713C) and 50° (EP715C) available.

Construction: Diecast construction for lasting quality and greater heat dissipation. High-quality powder coat finish prevents rust and paint cracking.

Installation: Hole cutout size: 2" (50 mm). Oak™ LED Light engines require driver. Can be utilized in new construction and remodel applications.

LED Technology: Extremely accurate color rendering with 93+ CRI. Efficacy of up to 104 lumens per watt. Lumen Maintenance of 50,000 hours L70 based on LM80. Superior Thermal Management by utilizing diecast aluminum body as heat sink.

Electrical: Requires driver. Driver and housing can be specified with voltage (120V or 120/277V) and dimming (ELV/Triac or 0-10V/Triac/ELV)

Compatible Housings/Delivered Lumens: Architectural Oak™ Light Engines are compatible with 120/277V 0-10V/Triac/ELV or 120V Triac/ELV Architectural Oak™ Housings.


•**Delivered Lumens:** 2700K: 850 lm, 3000K: 900 lm

Dimming: See Oak™ Housings and drivers for specific dimming information.


Listings: cUL Listed. UL Listed for Damp Location. UL Listed for direct contact with insulation. Airtight per ASTM E-283. ENERGY STAR® Qualified. California Title 24 (JA8-2016-E).

Warranty: ELCO Products are built to last with a 5-year Limited warranty.

Dimensions



Aperture Dimensions



Product Number Builder

Example: E1AK22F27B


| | | | | |
|-----------------------------------|--------------|---------------------------|----------------------|----------------------------|
| 1" Architectural Oak Downlight | Style | Beam Angle | Color Temperature | Finish |
| E1AK | | | | |
| | 22 Pull Down | F 38° NF 28° WF 50° | 27 2700K 30 3000K | W All White B All Black |

Compatible Products

For use with 1" Oak™ Architectural Recessed Adjustables




1" Oak™ New Construction Housings, Frames & Power Packs




R-60 IC Airtight Housing
- Driver Included -
New Construction

| CAT NO. | SPECIFICATIONS |
|---------------|---------------------------|
| E1ATB08AJIC | 120V, Triac/ELV |
| E1ATB08AJICDX | 120/277V, 0-10V/Triac/ELV |



IC Rated Frame
- Driver Included -
New Construction


| CAT NO. | SPECIFICATIONS |
|-------------|---------------------------|
| E1ATB08IC | 120V, Triac/ELV |
| E1ATB08ICDX | 120/277V, 0-10V/Triac/ELV |



IC Rated Power Pack
- Fits through 2" hole -
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|---------------------------|
| E1RLA08IC | 120V, Triac/ELV |
| E1RLA08ICDX | 120/277V, 0-10V/Triac/ELV |


Accessories for Remodel IC Power Pack



Single Downlight Frames
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|---------------------------------|
| E1LF2 | 2 3/8" Cutout, 4 5/8" Sq. frame |

*Requires Power Pack (not included)



Multiple Downlight Frames
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|--------------------------------------|
| E1LF2-M2 | 2-Set, 8 3/4" total length of frame |
| E1LF2-M3 | 3-Set, 13" total length of frame |
| E1LF2-M4 | 4-Set, 17 1/2" total length of frame |
| E1LF2-M5 | 5-Set, 21 3/4" total length of frame |

*Requires Power Pack (not included)

1" Oak™ Accessories




Trimless Rings

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| RMITLW | All White |
| RMITLB | All Black |
| RMITLBZ | All Bronze |



Lens & Optics

| CAT NO. | SPECIFICATIONS |
|---------|---|
| EP713C | 28° Lens |
| EP714C | 38° Lens |
| EP715C | 50° Lens |
| L60 | Frosted Diffuser (For E1AK02, E1AK12, & E1AK32) |
| L61 | Hex Louver (For E1AK02, E1AK12, & E1AK32) |



Fire Rated Products


| CAT NO. | SPECIFICATIONS |
|---|---|
| FIREENCL | Standard - 9" H x 20 3/8" L x 14 3/8" W |
| FIREENCL-S | Shallow - 7 1/4" H x 16" L x 14 3/8" W |
| 1-Hr Fire Enclosure for Recessed Fixtures | |
| FIRECVR | 9 3/4" H x 17" O.D. x 13" I.D. |
| 2-Hr Fire Cover for Recessed Fixtures | |

Photometric Report

1" Square Pull Down Recessed Architectural Oak™ Adjustable

PHOTOMETRIC REPORT

Product #: E1AK22F27
Wattage / Lumens: 8.1W / 850 lm
Luminaire LPW: 105 lm/W



CANDLE POWER SUMMARY

| Degree Vertical | 0° |
|-----------------|------|
| 0 | 1661 |
| 5 | 1606 |
| 15 | 1109 |
| 25 | 470 |
| 35 | 138 |
| 45 | 49 |
| 55 | 17 |
| 65 | 8 |
| 75 | 3 |
| 85 | 0 |
| 90 | 0 |

ILLUMINANCE AT A DISTANCE


| Distance to Target Plane | Center Beam Footcandles | Beam Diameter |
|--------------------------|-------------------------|---------------|
| 4' | 104 | 2.8' |
| 6' | 46.1 | 4.2' |
| 8' | 25.9 | 5.6' |
| 10' | 16.6 | 7.0' |

ZONAL LUMEN SUMMARY

| Zone | Lumens | %Luminaire |
|-------|--------|------------|
| 0-30° | 675.5 | 79.8 |
| 0-40° | 775.7 | 91.7 |
| 0-60° | 833.4 | 98.5 |
| 0-90° | 846.1 | 100 |

PHOTOMETRIC REPORT

Product #: E1AK22F30
Wattage / Lumens: 8.1W / 897 lm
Luminaire LPW: 110.7 lm/W



CANDLE POWER SUMMARY

| Degree Vertical | 0° |
|-----------------|------|
| 0 | 1756 |
| 5 | 1698 |
| 15 | 1173 |
| 25 | 497 |
| 35 | 146 |
| 45 | 52 |
| 55 | 18 |
| 65 | 8 |
| 75 | 4 |
| 85 | 0 |
| 90 | 0 |

ILLUMINANCE AT A DISTANCE

| Distance to Target Plane | Center Beam Footcandles | Beam Diameter |
|--------------------------|-------------------------|---------------|
| 4' | 110 | 2.8' |
| 6' | 48.8 | 4.2' |
| 8' | 27.4 | 5.6' |
| 10' | 17.6 | 7.0' |

ZONAL LUMEN SUMMARY

| Zone | Lumens | %Luminaire |
|-------|--------|------------|
| 0-30° | 714.4 | 79.8 |
| 0-40° | 820.3 | 91.7 |
| 0-60° | 881.3 | 98.5 |
| 0-90° | 894.8 | 100 |