

Project name:

Fixture type:

Date:

12V AC Retrofit Koto[™] LED Module

Works with 3" and 4" ELCO 12V AC Housings with 3" and 4" Koto™ Trims as a retrofit option



Features

- 9W, 800 lm, 3000K
- Works with 3" & 4" MR16 Bi-Pin Low Voltage Housings & Koto Trims 2 1/8" O.D. - 2 7/8" H
- Integrated 12V AC Dimmable Driver
- Works with Electronic and Magnetic 12V AC transformers
- Works in 3" and 4" ELCO Low Voltage Housings with GU5.3 Base.
- Excellent color rendering 93+ CRI
- Standard 38° Lens installed, 25° and 60° lens included with each module - Optional Lens: 18° (EP731C)
- Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47), Single Asymmetric Lens (L54), Double Asymmetric Lens (L55)
- Title 24 JA8-2019 Compliant
- Meets Energy Star Requirements
- Covered by U.S. PATENTS and Patents Pending

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated 12V AC driver and light engine. Diecast aluminum body with heat fins allow for efficient cooling.

Installation: Twist-lock design for toolless trim installation. Works in 3" and 4" ELCO Low Voltage Housings with GU5.3 Base using 3" and 4" Koto™ Trims.

Electrical: Module connects to 12V AC power supply. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Extremely accurate Color Rendering Index of 90+. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute

Dimmability: Dims down to 10% leading dimming

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Specifications

9W

800 lm

12V AC

LED

90

2700K - SunsetK

25° 38° 60°

Wattage

Lumens

Voltage

Color Temp


Lamp Type

Beam Angle

CRI

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com © ELCO Lighting 2025. All rights reserved • Rev. 05 Mar 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.


Dimensions



Product Numbers

Item	Lamp type	Lumens	сст	Watts	Voltage	Beam Angle
ELK0827-12	LED	800 lm	2700K	9W	12V AC	25°, 38°, 60°
ELK0830-12	LED	800 lm	3000K	9W	12V AC	25°, 38°, 60°
ELK08SD-12	LED	800 lm	SunsetK	9W	12V AC	25°, 38°, 60°

Product Number Builder Example: ELK0827-12




¹ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed



For use with Koto[™] 12V AC Retrofit LED Light Engine

For Retrofitting 3" Bi-Pin 12V AC GU5.3 Housings

EL2699REA



3" Low Voltage Housing **New Construction**

SPECIFICATIONS

Magnetic Transformer

Electronic Transformer

120V Magnetic Transformer

277V Magnetic Transformer

120V Electronic Transformer

CAT NO.

EL2699A

EL2699EA

EL2699LDICA

EL2699-277A

EL2699LDICEA



	3" Low Voltage Housing Remodel
).	SPECIFICATIONS

	Remodel	
CAT NO.	SPECIFICATIONS	CA
EL2699LDRICA	Magnetic Transformer	EL
EL2699LDRICEA	Electronic Transformer	EL.
EL2699RA	120V Magnetic Transformer	
EL2699R-277A	277V Magnetic Transformer	

120V Electronic Transformer



3" Low Voltage Housing **New Construction**

	CAT NO.	SPECIFICATIONS
	EL2699ICA	Magnetic Transformer, 50W Max.
	EL2699ICEA	Electronic Transformer, 50W Max.
-		
		Recommended to be used with Maximum Adjustability Housing
	••••••	
R		
e Pi	nhole	Round Adj. Slot Aperture
		ELK3620
, H)		Finishes: (W)
efle	ector	Round Directional Gimbal
		ELK3679

3″ Pex™ Twist-On Trims



*Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring



For use with Koto[™] 12V AC Retrofit LED Light Engine 3" Pex[™] Flush Mount Trim Adaptors



Round Flush Mount Trim Adaptor

EL3FMR Compatible 3" Pex™ Round trims: ELK3618, ELK3629, ELK3627, ELK3693, ELK3620, ELK3622 Series

3" Pex[™] Trimless



Square Flush Mount Trim Adaptor EL3FMS

Compatible 3″ Pex™ Square trims: ELK3318, ELK3329, ELK3322, ELK3327, ELK3341, ELK3393 Series







Round Trimless Reflector ELK308

Finishes: (W, B, H)



Square Trimless Reflector ELK370 Finishes: (W, B, H)



Round Adjustable Trimless Reflector ELK315 Finishes: (W, B, H)



Square Adjustable Trimless Reflector ELK381 Finishes: (W, B, H)



Spackle Frame EL3SFR For use with ELK315



Square Trimless Spackle Frame EL03SFS For use with ELK370 & ELK381

Round Knife Edge Wood Ceiling Trim w/Mounting Clips EL3WCR Finishes: (W, B)

Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B* - All Black (For ELK376, & ELK370, & ELK370, & ELK370).



.....

Recommended to be used with Maximum Adjustability Housing

For use with Koto[™] 12V AC Retrofit LED Light Engine

For Retrofitting 4" Bi-Pin 12V AC GU5.3 Housings


CAT NO.

EL1499LDRICA

E1499LDRICEA

EL1499RA

EL1499REA



4" Low Voltage Housing **New Construction**

SPECIFICATIONS

Magnetic Transformer

Electronic Transformer

Magnetic Transformer, 50W

Magnetic Transformer, 50W

Electronic Transformer, 50W

CAT NO.

EL1499A

EL1499EA

EL1499LDICA

EL1499-277A

EL1499LDICEA

	7	
J		h
		\geq

4" Low Voltage Housing Remodel

SPECIFICATIONS

Magnetic Transformer

Electronic Transformer

Magnetic Transformer

Electronic Transformer



4" Low Voltage Housing **New Construction**


CAT NO.	SPECIFICATIONS
EL1499ICA	Magnetic Transformer, 50W
EL1499ICA-277	Magnetic Transformer, 50W
EL1499ICA-L	Magnetic Transformer, 50W
EL1499ICEA	Electronic Transformer, 50W

Shallow	Deep	Adjustable	Adjustable Reflector	Adjustable Reflector
Reflector	Reflector	Reflector	with Clear Glass	with Frosted Lens
ELK4116	ELK4118	ELK4129	ELK4111	ELK4112
Finishes:	Finishes:	Finishes:	Finishes:	Finishes:
(W, H)	(W, BB, BZ, B, C, H)	(W, BB, BZ, B, C, H)	(W, BB, BZ, B, C, H)	(W, BB, BZ, B, C, H)
Rotatable Slot Aperture ELK4120 Finishes: (W)	Adjustable Wall Wash ELK4122 Finishes: (W)	Adjustable Pinhole ELK4127 Finishes: (W, BB, BZ, B, H)	Adjustable Pinhole with Frosted Glass ELK4125 Finishes: (W, BB, BZ, B, H)	Slot Aperture ELK4130 Finishes: (W)
Adjustable Spot	Regressed Eyeball	Curved Reflector	Directional Gimbal	Adjustable Baffle
ELK4188	ELK4153	ELK4172	ELK4179	ELK4193
Finishes:	Finishes:	Finishes:	Finishes:	Finishes:
(W, B, BZ)	(W, BB, B)	(W, B)	(W, BB, B, H)	(W, BB, B)

*Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring

For use with Koto[™] 12V AC Retrofit LED Light Engine





*Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black Reflector w/White Ring, C - Chrome Reflector w/White Ring, H - Haze Reflector w/White Ring

For use with Koto[™] 12V AC Retrofit LED Light Engine



4″ Flexa™ Twist-On Trims





Round Reflector

ELK4721 Finishes: (WW, BB, BZBZ, BW, CW, HW)



Finishes: (WW, BB, BZBZ, BW)



, BW)



Square Reflector

ELK4741 Finishes: (WW, BB, BZBZ, BW, HW) *Not for Remodel Housing

		~~	1
		1	
S	quare	Baffle	2

ELK4743 Finishes:

.....

(WW, BB, BZBZ, BW) *Not for Remodel Housing



Square Adj. Reflector ELK4759 Finishes:

(WW, BB, B, H)

*Not for Remodel Housing

.....

Finishes: W - All White, BB - All Black, BZ - All Bronze, B - Black w/White Ring, C - Chrome w/White Ring, H - Haze w/White Ring, B* - All Black (For ELK408, ELK415, ELK45, ELK415, ELK45, ELK45, ELK45, ELK45, ELK45

4" Unique™ Twist-On Trims




Finishes: W - All White, B - All Black, BZ - All Bronze


Photometric Report

12V AC Retrofit Koto[™] LED Module

PHOTOMETRIC REPORT

Product #: ELK0830-12 Wattage / Lumens: 10W / 971.7 Im Luminaire LPW: 97 Im/W





CANDLE POWER SUMMARY

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	103.3	3.1′
6'	36.4	4.7′
8'	18.7	6.3'
10′	12.6	7.8′

ZONAL LUMEN SUMMARY

-

_

_

Zone	Lumens	%Luminaire
0-30°	565.3	70.6
0-40°	697.3	87.1
0-60°	780.3	97.5
0-90°	796.0	99.4