

2" LED Round Baffle




Features

- IC rated for direct connect with insulation
- 8W
- CRI 90+
- 120V
- ETL listed
- ENERGY STAR compliant
- Dimmable Triac/ELV

Specifications

Wattage	8W
Lumens	600 lm
Color Temp.	2700K, 3000K, 3500K - 3000K
Lamp Type	LED
CRI	90+
Wet Location	Listed

Dimensions



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Finish
ERT21430W	LED	600 lm	3000K	8W	White
ERT214CT3W	LED	600 lm	2700K, 3000K, 3500K	8W	White

Product Number Builder Example: ERT21430W

LED Round Baffle	Color Temperature	Finish
ERT214	30 3000K CT3 2700K-3500K	W White

Compatible Products

For use with 2" Elm™ System Downlights

2" Elm™ New Construction Frames



New Construction Frame for Slim Panels
Single Cutout

CAT NO.	SPECIFICATIONS
E2LF1	2" Frame



New Construction Frame for Slim Panels
Multiple Cutout

CAT NO.	SPECIFICATIONS
E2LF1-M2	2 Set
E2LF1-M3	3 Set
E2LF1-M4	4 Set
E2LF1-M5	5 Set



Universal Frame for 2", 4" and 6"
New Construction

CAT NO.	SPECIFICATIONS
E246LF1	For 2", 4" and 6"

2" Elm™ Accessories



Extension Cords

CAT NO.	SPECIFICATIONS
ECNE10	10" Long
ECNE11	10' Ft Long