

2" Square Adjustable LED Teak™ Light



Features

- 35° Adjustability
- Damp Location Rated
- Same LED light engine for 850 and 1100 lumens (see housings)
- UL Listed for Direct Contact with insulation
- Standard with 38° beam. Field Changeable optics for 28° (EP716C) and 60° (EP718C)
- CAT24, JA8-2016-E and Energy Star Listed
- Life Span 50,000 Hours L70

Specifications

Wattage	8.6 - 10.5W
Lumens	850 - 1100 lm
Color Temp.	2700K - 3000K
Lamp Type	LED
Beam Angle	38°
CRI	93+
Wet Location	Listed

Options



White



All Bronze



All Black

Technical Details

Optics: 35° Adjustability. Standard with 38° beam. Field changeable optics for 28° (EP716C) and 60° (EP718C)

Construction: Diecast construction for lasting quality and greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: All Teak™ LED Light Engines feature a trigger release clip that will depress as the module is being inserted, holding the module in place.

LED Technology:

- Extremely accurate color rendering with 93+ CRI.
- Efficacy of max. 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 based on LM80 standardized test results.
- Superior Thermal Management by utilizing aluminum body as heat sink.


Electrical: Low voltage input. Requires compatible power supply.

Dimming: Works with Triac/ELV type dimmers when powered by 120V driver. Works with 0-10V/Triac/ELV dimmers when powered by 120/277V driver.

Listings: UL Listed for Damp Location. UL Listed for Direct Contact with insulation. ENERGY STAR® Listed. California Title 24 (JA8-2016-E).

Warranty: ELCO Products are built to last with a 5-year Limited warranty.

Dimensions



Product Numbers

Item	Description	Lamp type	Lumens	CCT	Watts	Beam Angle	Finish
E2L19F27W	Adjustable	LED	850 - 1100 lm	2700K	8.6 - 10.5W	38°	White
E2L19F30W	Adjustable	LED	850 - 1100 lm	3000K	8.6 - 10.5W	38°	White
E2L19F27B	Adjustable	LED	850 - 1100 lm	2700K	8.6 - 10.5W	38°	All Black
E2L19F30B	Adjustable	LED	850 - 1100 lm	3000K	8.6 - 10.5W	38°	All Black
E2L19F27BZ	Adjustable	LED	850 - 1100 lm	2700K	8.6 - 10.5W	38°	All Bronze
E2L19F30BZ	Adjustable	LED	850 - 1100 lm	3000K	8.6 - 10.5W	38°	All Bronze

Product Number Builder Example: E2L19F27W

Square Adjustable	Beam Angle	Color Temperature	Finish
E2L19	F 38°	27 2700K	W All White

NF 28°
WF 60°

30 3000K
35 3500K
40 4000K

B All Black
BZ All Bronze