

# 2" Square LED Teak™ Baffle



## Features

- Wet Location Rated for Indoor and Outdoor Use (Under covered ceilings)
- Same LED light engine for 850 and 1100 lumens (see housings)
- UL Listed for Direct Contact with insulation
- Standard with 38° beam. Field Changeable optics for 28° (EP716C) and 60° (EP718C)
- CAT24, JA8-2016-E and Energy Star Listed
- Life Span 50,000 Hours L70
- U.S. Pat. 10,125,959

## Specifications

<b>Wattage</b>	8.6 - 10.5W
<b>Lumens</b>	850 - 1100 lm
<b>Color Temp.</b>	2700K - 3000K
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	38°
<b>CRI</b>	93+
<b>Wet Location</b>	Listed

## Options



All White



All Bronze



Black/White



All Black

## Technical Details

**Optics:** Standard with 38° beam. Field changeable optics for 28° (EP716C) and 60° (EP718C)

**Construction:** Diecast construction for lasting quality and greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

**Installation:** All Teak™ LED Light Engines feature a trigger release clip that will depress as the module is being inserted, holding the module in place.

### LED Technology:

- Extremely accurate color rendering with 93+ CRI.
- Efficacy of max. 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 based on LM80 standardized test results.
- Superior Thermal Management by utilizing aluminum body as heat sink.


**Electrical:** Low voltage input. Requires compatible power supply.

**Dimming:** Works with Triac/ELV type dimmers when powered by 120V driver. Works with 0-10V/Triac/ELV dimmers when powered by 120/277V driver.

**Listings:** UL Listed for Wet Location. UL Listed for Direct Contact with insulation. ENERGY STAR® Listed. California Title 24 (JA8-2016-E).

**Warranty:** ELCO Products are built to last with a 5-year Limited warranty.

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Beam Angle	Finish
<b>E2L15F27W</b>	LED	850 - 1100 lm	2700K	8.6 - 10.5W	38°	White
<b>E2L15F30W</b>	LED	850 - 1100 lm	3000K	8.6 - 10.5W	38°	White
<b>E2L15F27B</b>	LED	850 - 1100 lm	2700K	8.6 - 10.5W	38°	Black/White
<b>E2L15F30B</b>	LED	850 - 1100 lm	3000K	8.6 - 10.5W	38°	Black/White

Item	Lamp type	Lumens	CCT	Watts	Beam Angle	Finish
<b>E2L15F27BZ</b>	LED	850 - 1100 lm	2700K	8.6 - 10.5W	38°	All Bronze
<b>E2L15F30BZ</b>	LED	850 - 1100 lm	3000K	8.6 - 10.5W	38°	All Bronze

## Product Number Builder Example: **E2L15F27W**

2" Square Baffle	Beam Angle	Color Temperature	Finish
<b>E2L15</b>			
	<b>F</b> 38° <b>NF</b> 28° <b>WF</b> 60°	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>W</b> All White <b>BZ</b> All Bronze <b>B</b> Black/White <b>BB</b> All Black