

24V DC 3" Remodel Dedicated LED IC Airtight Housing



24V DC 3" remodel dedicated LED housing. Compatible with 24V DC Koto™ Module.


Features

- Only for use with [24V DC Koto Module](#)
- IC Airtight for direct contact with insulation.
- Flicker Free LED Dimming.
- Simple installation with 24V Wire.
- Trims and module sold separately.

Specifications

| | |
|----------------------|--------------------------|
| Wattage | 14W |
| Voltage | 24V DC |
| Wet Location | Listed with Shower Trims |
| Damp Location | Listed |

Dimensions



Technical Details

Construction:

- Single wall IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x6 joists or taller joists are used. Maximum hole cutout is 3 5/8". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Electrical:

- Input Voltage: 24V DC.
- Thermally protected against improper lamping.

Lamp: Designed for use with 24V DC Koto Module and trims.

Listings:

- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2022-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

Product Number

| Item | Watts | Voltage |
|-------------|-------|---------|
| E24V390RICA | 14W | 24V DC |

Compatible Products

For use with Dedicated 3" 24V DC ICA New Construction Housings

Koto™ 24V DC LED Light Engine



24V DC Koto™ LED Light Engine

| PRODUCT NUMBER BUILDER | | | |
|------------------------|-----------|----------------------|------------|
| Koto™ LED Light Engine | Lumens | Color Temperature | Voltage |
| ELK | 08 800 lm | 27 2700K 30 3000K | -24 24V DC |

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

ACCESSORIES



Lens

- EP731C 18° Lens
 - EP732C 25° Lens
 - EP733C 38° Lens
 - EP734C 60° Lens
- *EP732C, EP733C, EP734C Included with standard module



Snout

- L50W White
- L50B Black



Secondary Optics

- L45 Hex Louver
- L46 Linear Lens
- L47 Spread Louver
- L49 Frosted Lens
- L51 Color Shifter
- L57 White Hex Louver
- L52 Blue Lens
- L53 Pink Shifter

3" Pex™ Twist-On Trims



Recommended to be used with Maximum Adjustability Housing



Round Deep Reflector

ELK3618
Finishes:
(W, BB, BZ, B, C, H)



Round Adjustable Gimbal

ELK3629
Finishes:
(W, BB, BZ, B, C, H)



Round Adjustable Pinhole

ELK3627
Finishes:
(B, BB, BZ)



Round Adjustable Baffle

ELK3693
Finishes:
(W)




Round Adj. Slot Aperture

ELK3620
Finishes:
(W)




Round Adj. Wall Wash

ELK3622
Finishes:
(W)



Square Deep Reflector

ELK3318
Finishes:
(W, BB, BZ, B, C, H)




Square Adjustable Gimbal

ELK3329
Finishes:
(W, BB, BZ, B, C, H)




Square Adjustable Pinhole

ELK3327
Finishes:
(B, BB, BZ)




Square Reflector

ELK3341
Finishes:
(W, B, BB, BZ)



Square Adj. Wall Wash

ELK3322
Finishes:
(W)



Square Adjustable Baffle

ELK3393
Finishes:
(W)

Compatible Products

For use with Dedicated 3" 24V DC ICA New Construction Housings

3" Pex™ Trimless *• Only for use with E24V386ICA*



Spackle Frame

EL3SFR



Adjustable Trimless Reflector

ELK315

Finishes:


(W, B, H)

3" Flush Mount Trim Adaptors



Round Flush Mount

EL3FMR



Square Flush Mount

EL3FMS

Compatible Products

For use with Dedicated 3" 24V DC ICA New Construction Housings

24V DC Transformers



**Electronic Low Voltage
Dimmable Driver**

| CAT NO. | SPECIFICATIONS |
|------------|-----------------|
| DRVE24V60W | 60W, 120V Input |



**Constant Voltage
LED Driver**

| CAT NO. | SPECIFICATIONS |
|---------|----------------------|
| DRV60W | 60W, 120/277V Input |
| DRV100W | 100W, 120/277V Input |



**0-10V
Dimmable Driver**

| CAT NO. | SPECIFICATIONS |
|-----------|---------------------|
| DRV30W-10 | 30W, 120/277V Input |
| DRV60W-10 | 60W, 120/277V Input |
| DRV96W-10 | 96W, 120/277V Input |




**Lutron™ Hi-Lume 1%
LED Driver**

| CAT NO. | SPECIFICATIONS |
|-----------|------------------------------------|
| DRVLT40W | 40W, Triac, 120/277V |
| DRVLT340W | 40W, Lutron Ecosystem, 120/277V |



**Lutron™ Hi-Lume Premiere 0.1%
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|----------|--|
| DRVL396W | 96W, Lutron Ecosystem, 120/277V Input |



**Universal (Small)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|-------------|--------------------------------------|
| DRVU24V24WD | 24W, 24V DC (1A), Triac/ELV/MLV |
| DRVU24V60WD | 60W, 24V DC (2.5A), Triac/ELV/MLV |



**Universal (Medium)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|--------------|-------------------------------------|
| DRVU24V100WD | 100W, 24V DC (4A), Triac/ELV/MLV |




**Universal (Large)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|--------------|-------------------------------------|
| DRVU24V200WD | 200W, 24V DC (8A), Triac/ELV/MLV |



**Universal (X-Large)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|--------------|--------------------------------------|
| DRVU24V300WD | 300W, 24V DC (12A), Triac/ELV/MLV |



**Electronic (Large)
Dimming LED Driver**

| CAT NO. | SPECIFICATIONS |
|-------------|---------------------------|
| DRVE24V48DW | 48W, 24V DC (2A), Triac |
| DRVE24V60DW | 60W, 24V DC (2.5A), Triac |
| DRVE24V96DW | 96W, 24V DC (4A), Triac |



**Dimmer
with Built-in Driver**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| DIMTP2 | 60W, 120V |
| DIMTP3 | 100W, 120V |