


3" 0-10V New Construction Dedicated LED IC Airtight Housing



3" New Construction LED Housing compatible with 0-10V LED Koto™ Module.



Features

- Wired for 0-10V Dimming
- 120/277V Input
- Single Wall IC Airtight Housing for use in insulated ceilings
- cUL Listed for direct contact with Insulation

Specifications

Voltage	120/277V
Dimmable	0-10V/Triac/ELV
Damp Location	Listed

Dimensions



Technical Details

Construction:

- Single Wall IC rated for direct contact with insulation, for use in IC or Non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x6 joists or taller joists are used. High strength hanger bars can easily be nailed to joists. Maximum hole cutout is 3 5/8". Suitable for t-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts, four 3/4" knockouts. Pry-out knockout slots. 4 Romex pryouts with strain relief.

Hanger Bars: Pre-installed hanger bars with True Nail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housings with the joists.

Electrical: Input Voltage: 120/277V

Dimmability: Dimmability based on lamp.

Listings:

- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.


Product Numbers

Item	Description	Voltage	Dimming
EL390ICDXA		120/277V	0-10V/Triac/ELV
EL390ICDXA-EM5	Emergency Battery Backup (90 minute)	120/277V	0-10V/Triac/ELV

Compatible Products

For use with Dedicated 3" 0-10V Koto ICAD LED Housings

0-10V Koto™ LED Module



0-10V Koto™
LED Module
ELK10DX

PRODUCT NUMBER BUILDER				
0-10V Koto™ LED Module	Lumens	Voltage	Color Temperature	Beam Angle
ELK				
	10 1000 lm	DX 120/277V	27 2700K	(blank) 38° lens (Standard)
			30 3000K	-S 18° lens
			35 3500K	-N 25° lens
			40 4000K	-W 60° lens
			SD Sunset Dimming	

ACCESSORIES



Lens

- EP731C 18° Lens
 - EP732C 25° Lens
 - EP733C 38° Lens
 - EP734C 60° Lens
- *EP732C, EP733C, EP734C Included



Snoot

- L50W White
- L50B Black



Secondary Optics

- L45 Hex Louver
- L46 Linear Lens
- L47 Spread Louver
- L49 Frosted Lens
- L51 Color Shifter

3" Pex™ Twist-On Trims




Recommended to be used with Maximum Adjustability Housing



Round Deep Reflector

ELK3618
Finishes:
(W, BB, BZ, B, C, H)




Round Adjustable Gimbal

ELK3629
Finishes:
(W, BB, BZ, B, C, H)



Round Adjustable Pinhole

ELK3627
Finishes:
(B, BB, BZ)



Round Adjustable Baffle

ELK3693
Finishes:
(W)




Round Adj. Slot Aperture

ELK3620
Finishes:
(W)




Round Adj. Wall Wash

ELK3622
Finishes:
(W)



Square Deep Reflector

ELK3318
Finishes:
(W, BB, BZ, B, C, H)



Square Adjustable Gimbal

ELK3329
Finishes:
(W, BB, BZ, B, C, H)




Square Adjustable Pinhole

ELK3327
Finishes:
(B, BB, BZ)




Square Reflector

ELK3341
Finishes:
(W, B, BB, BZ)



Square Adj. Wall Wash

ELK3322
Finishes:
(W)




Square Adjustable Baffle

ELK3393
Finishes:
(W)

Compatible Products

For use with Dedicated 3" 0-10V Koto ICAD LED Housings

3" Pex™ Trimless Only for use with EL386/CDXA



Spackle Frame

EL3SFR




Adjustable Trimless Reflector

ELK315


Finishes:
(W, B, H)

3" Flush Mount Trim Adaptors



Round Flush Mount


EL3FMR



Square Flush Mount

EL3FMS

3" Accessories



Emergency Battery Backup


CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V

* Requires access from above




Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L