

3" Knife Edge Wood Ceiling Trim

With Mounting Clips for use with Round Flush Mount Koto Trim Adaptor



Features

- Compatible with 3" Adjustable Trimless Reflector (ELK315) and with 3" Fixed Trimless Reflector (ELK308). Sold Separately
- 3" Die-Cast Round Adaptor with Mounting Clips.
- Compatible with ceilings up to 2" thick
- 3 7/8" O.D.
- Lamp: Koto™ LED Module and Canless Koto™ LED Module.

Technical Details

Construction: Diecast aluminum with a powder-coated finish.

Installation: For use with 3" Trimless Smooth Reflector (ELK315W) or with 3" Fixed Trimless Reflector (ELK308). Sold separately. Compatible with ceilings up to 2" thick. Remove collar from housing before installing.

Lamp: Koto™ LED Module and Canless Koto™ LED Module.

Options




White



Black

Dimensions



Product Numbers

Item	Finish
EL3WCRW	All White
EL3WCRB	All Black

Product Number Builder Example: EL3WCRW

3" Knife Edge Wood Ceiling Trim

Color Finish


EL3WCR

- W** All White
- B** All Black

Compatible Products

For use with 3" Koto™ Twist-&-Lock Trimless

Koto™ LED Module



Koto™ LED Module
ELK07, ELK09, & ELK11

PRODUCT NUMBER BUILDER					
Koto™ LED Module	Lumens	Color Temperature	Beam Angle		
ELK					
07	750 lm	27 2700K	(blank)	38° lens (Standard)	
09	950 lm	30 3000K	-S	18° lens	
11	1150 lm	35 3500K	-N	25° lens	
		40 4000K	-W	60° lens	
		SD Sunset Dimming (For ELK09 & ELK11)	-FC	18° - 50° Adjustable (ELK07 Only)	

ACCESSORIES



Lens

- EP731C** 18° Lens
- EP732C** 25° Lens
- EP733C** 38° Lens
- EP734C** 60° Lens

*EP732C, EP733C, EP734C Included




Snoot

- L50W** White
- L50B** Black



Secondary Optics

- L45** Hex Louver
- L46** Linear Lens
- L47** Spread Louver
- L49** Frosted Lens
- L51** Color Shifter




Koto™ LED Module with 5-CCT Switch



Product Number

- ELK08CT5** 825 lm
- ELK10CT5** 1000 lm

3" Koto™ Dedicated LED ICA Housings



3" ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
EL386ICA	Maximum Adjustability

3" Pex™ Trimless



Round Trimless Reflector
ELK308
Finishes:
(W, B, H)




Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)

Compatible Products

For use with 3" Koto™ Twist-&-Lock Trimless

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

PRODUCT NUMBER BUILDER			
Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
19	750 - 850 lm	27D 2700K	(blank) 38° lens (Standard)
21	1100 - 1500 lm	30D 3000K	-S 18° lens
		35D 3500K	-N 25° lens
		40D 4000K	-W 60° lens
		SD Sunset Dimming (ELK19 Only)	-FC 18° - 50° Adjustable (ELK21 Only)

ACCESSORIES



Lens

- EP731C** 18° Lens
- EP732C** 25° Lens
- EP733C** 38° Lens
- EP734C** 60° Lens

*EP732C, EP733C, EP734C Included



Shoot


- L50W** White
- L50B** Black




Secondary Optics

- L45** Hex Louver
- L46** Linear Lens
- L47** Spread Louver
- L49** Frosted Lens
- L51** Color Shifter

3" Koto™ Architectural Recessed Housings



3" High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
Not for use with ELK19 Series Module
New Construction




3" Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
E3LK53ICA	15.7W - 120V - Triac/ELV	E3LK76ICA	120V - Triac/ELV
E3LK54ICAD	15.7W - 120/277V 0-10V/Triac/ELV	E3LK77ICAD	120/277V - 0-10V/Triac/ELV
E3LK85ICAD	18.9W - 120/277V 0-10V/Triac/ELV		

3" Pex™ Trimless



Round Trimless Reflector
ELK308
Finishes:
(W, B, H)



Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)