

3" Knife Edge Wood Ceiling Trim

With Mounting Clips for use with Round Flush Mount Koto Trim Adaptor



Features

- Compatible with 3" Adjustable Trimless Reflector (ELK315) and with 3" Fixed Trimless Reflector (ELK308). Sold Separately
- 3" Die-Cast Round Adaptor with Mounting Clips.
- Compatible with ceilings up to 2" thick
- 3 7/8" O.D.
- Lamp: Koto™ LED Module and Canless Koto™ LED Module.

Technical Details

Construction: Diecast aluminum with a powder-coated finish.

Installation: For use with 3" Trimless Smooth Reflector (ELK315W) or with 3" Fixed Trimless Reflector (ELK308). Sold separately. Compatible with ceilings up to 2" thick. Remove collar from housing before installing.

Lamp: Koto™ LED Module and Canless Koto™ LED Module.


Options



White

Black

Dimensions



Product Numbers

| Item | Finish |
|---------|-----------|
| EL3WCRW | All White |
| EL3WCRB | All Black |

Product Number Builder Example: EL3WCRW

3" Knife Edge Wood Ceiling Trim

Color Finish


EL3WCR

- W** All White
- B** All Black

Compatible Products

For use with 3" Koto™ Twist-&-Lock Trimless

Koto™ LED Module



Koto™ LED Module
ELK07, ELK09, & ELK11

| PRODUCT NUMBER BUILDER | | | | | |
|------------------------|---------|---------------------------------------|---------------------------------------|--|--|
| Koto™ LED Module | Lumens | Color Temperature | Beam Angle | | |
| ELK | | | | | |
| 07 | 750 lm | 27 2700K | (blank) 38° lens (Standard) | | |
| 09 | 950 lm | 30 3000K | -S 18° lens | | |
| 11 | 1150 lm | 35 3500K | -N 25° lens | | |
| | | 40 4000K | -W 60° lens | | |
| | | SD Sunset Dimming (For ELK09 & ELK11) | -FC 18° - 50° Adjustable (ELK07 Only) | | |

ACCESSORIES



Lens

- EP731C 18° Lens
- EP732C 25° Lens
- EP733C 38° Lens
- EP734C 60° Lens

*EP732C, EP733C, EP734C Included




Snoot

- L50W White
- L50B Black




Secondary Optics

- L45 Hex Louver
- L46 Linear Lens
- L47 Spread Louver
- L49 Frosted Lens
- L51 Color Shifter




Koto™ LED Module with 5-CCT Switch



Product Number

| | |
|----------|---------|
| ELK08CT5 | 825 lm |
| ELK10CT5 | 1000 lm |

3" Koto™ Dedicated LED ICA Housings



3" ICA Maximum Adjustability Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|-----------------------|
| EL386ICA | Maximum Adjustability |

3" Pex™ Trimless



Round Trimless Reflector
ELK308
Finishes:
(W, B, H)




Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)

Compatible Products

For use with 3" Koto™ Twist-&-Lock Trimless

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

| PRODUCT NUMBER BUILDER | | | |
|------------------------|----------------|--------------------------------|---------------------------------------|
| Koto™ LED Light Engine | Lumens | Color Temperature | Beam Angle |
| ELK | | | |
| 19 | 750 - 850 lm | 27D 2700K | (blank) 38° lens (Standard) |
| 21 | 1100 - 1500 lm | 30D 3000K | -S 18° lens |
| | | 35D 3500K | -N 25° lens |
| | | 40D 4000K | -W 60° lens |
| | | SD Sunset Dimming (ELK19 Only) | -FC 18° - 50° Adjustable (ELK21 Only) |

ACCESSORIES



Lens

- EP731C** 18° Lens
- EP732C** 25° Lens
- EP733C** 38° Lens
- EP734C** 60° Lens

*EP732C, EP733C, EP734C Included



Shoot


- L50W** White
- L50B** Black




Secondary Optics

- L45** Hex Louver
- L46** Linear Lens
- L47** Spread Louver
- L49** Frosted Lens
- L51** Color Shifter

3" Koto™ Architectural Recessed Housings



3" High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
Not for use with ELK19 Series Module
New Construction



3" Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

| CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS |
|------------|-------------------------------------|------------|----------------------------|
| E3LK53ICA | 15.7W - 120V - Triac/ELV | E3LK76ICA | 120V - Triac/ELV |
| E3LK54ICAD | 15.7W - 120/277V 0-10V/Triac/ELV | E3LK77ICAD | 120/277V - 0-10V/Triac/ELV |
| E3LK85ICAD | 18.9W - 120/277V 0-10V/Triac/ELV | | |

3" Pex™ Trimless



Round Trimless Reflector
ELK308
Finishes:
(W, B, H)



Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)