

3" Non-IC Airtight Remodel Housing with Driver




Features

- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- Flicker-Free Dimming.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 3" LED Light Engines.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

| | |
|---------------|----------|
| Lumens | 1000 lm |
| Voltage | 120/277V |
| Dimmable | Sunset |
| Power Factor | ≥0.95 |
| Damp Location | Listed |

Dimensions



Technical Details

Construction:

- Non-IC Frame for non-IC conditions.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

Installation:

- Designed for ceiling plenums where 2x6 joists or taller are used.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.95.

Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 5% with compatible dimmer.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For full list of dimmers refer to the Dimmer Compatibility List.

Listings: cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Feed Through.

Product Number

| Item | Lumens | Voltage | Dimming |
|-----------|---------|----------|---------|
| E3LRC10SD | 1000 lm | 120/277V | Sunset |

Product Number Builder Example: E3LRC082

ELCO Cedar 3" Remodel Housing

Lumens

Dimming

Generation

Optional

| | | | | |
|------------|---------------------------|---------|-------------------------------|--|
| E3LRC | | | | |
| 08 850 lm | 120V Triac/ELV | 2 Gen 2 | No EM | |
| 10 1000 lm | D 120/277V Triac/ELV0-10V | Gen 1 | EM1 Emer. Backup up to 700 lm | |
| | SD Sunset | | EM2 Emer. Backup to 1100 lm | |
| | L Lutron | | | |

Compatible Products

For use with 3" Cedar™ Non-IC LED housings



3" Cedar™ LED Light Engines



Round Reflector Trim

E310C

Finishes:

(W, B, BB, BZ, C, H)



Round Baffle Trim

E314C

Finishes:

(W, B, BB, BZ)



Square Pinhole Trim

E315C

Finishes:

(W, B, C)



Square Reflector Trim

E320C

Finishes:

(W, BB, BZ, C)



Round Pinhole Trim

E329C

Finishes:

(W, B, C)

PRODUCT NUMBER BUILDER

| 3" Cedar™ Trim | Style | Lumen | Color Temperature | Finish |
|----------------|-----------------------------|-------------------|--------------------------|------------------------------|
| E3 | | | | |
| | 10C Round Reflector | 08 850 lm | 27 2700K | W All White |
| | 14C Round Baffle | 10 1000 lm | 30 3000K | B Black w/White Ring |
| | 15C Square Pinhole | | 35 3500K | BB All Black |
| | 20C Square Reflector | | 40 4000K | BZ All Bronze |
| | 29C Pinhole Trim | | 50 5000K | C Chrome w/White Ring |
| | | | SD Sunset Dimming | H Haze w/White Ring |

3" Accessories



Fire Cover

| CAT NO. | SPECIFICATIONS |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |



Fire Enclosure

| CAT NO. | SPECIFICATIONS |
|------------|-------------------------------|
| FIREENCL | 20 3/8" L x 14 3/8" W |
| FIREENCL-S | Shallow, 16" L x 14 3/8" W |



Mica Fire Tape

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |