

# 3" Remodel Dedicated LED IC Airtight Housing

3" remodel dedicated LED housing. Compatible with PSA37 MR16 LED Lamps or 3" LED inserts.




## Features

- IC Airtight for direct contact with insulation.
- Flicker Free LED Dimming.
- Trims and inserts sold separately.

## Specifications

|                      |                          |
|----------------------|--------------------------|
| <b>Wattage</b>       | 14W                      |
| <b>Voltage</b>       | 120V                     |
| <b>Wet Location</b>  | Listed with Shower Trims |
| <b>Damp Location</b> | Listed                   |

## Dimensions



## Technical Details

### Construction:

- Single wall IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

**Installation:** Designed for ceiling plenums where 2x6 joists or taller joists are used. Maximum hole cutout is 3 5/8". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

### Electrical:

- Input Voltage: 120V AC.
- Thermally protected against improper lamping.

**Lamp:** Designed for use with PSA37 MR16 LED Lamps or 3" LED inserts

### Dimmability:

- Dimmability based on lamp.

### Listings:

- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

**Warranty:** ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.


## Product Numbers

| Item      | Watts | Voltage |
|-----------|-------|---------|
| EL390RICA | 14W   | 120V    |

# Compatible Products

For use with Dedicated 3" IC LED Housings

## Koto™ LED Module



**Koto™ LED Module**  
ELK07, ELK09, & ELK11

| PRODUCT NUMBER BUILDER |         |                                       |                                       |  |  |
|------------------------|---------|---------------------------------------|---------------------------------------|--|--|
| Koto™ LED Module       | Lumens  | Color Temperature                     | Beam Angle                            |  |  |
| ELK                    |         |                                       |                                       |  |  |
| 07                     | 750 lm  | 27 2700K                              | (blank) 38° lens (Standard)           |  |  |
| 09                     | 950 lm  | 30 3000K                              | -S 18° lens                           |  |  |
| 11                     | 1150 lm | 35 3500K                              | -N 25° lens                           |  |  |
|                        |         | 40 4000K                              | -W 60° lens                           |  |  |
|                        |         | SD Sunset Dimming (For ELK09 & ELK11) | -FC 18° - 50° Adjustable (ELK07 Only) |  |  |

### ACCESSORIES

**Lens**

**EP731C** 18° Lens  
**EP732C** 25° Lens  
**EP733C** 38° Lens  
**EP734C** 60° Lens  
\*EP732C, EP733C, EP734C Included

**Snoot**

**L50W** White  
**L50B** Black

**Secondary Optics**

**L45** Hex Louver  
**L46** Linear Lens  
**L47** Spread Louver  
**L49** Frosted Lens  
**L51** Color Shifter

**Koto™ LED Module with 5-CCT Switch**

**Product Number**

|                 |         |
|-----------------|---------|
| <b>ELK08CT5</b> | 825 lm  |
| <b>ELK10CT5</b> | 1000 lm |

## 3" Pex™ Twist-On Trims

**Deep Reflector**  
**ELK3618**  
 Finishes:  
 (W, BB, BZ, B, C, H)

**Adjustable Gimbal**  
**ELK3629**  
 Finishes:  
 (W, BB, BZ, B, C, H)

**Adjustable Pinhole**  
**ELK3627**  
 Finishes:  
 (B, BB, BZ)

**Adjustable Baffle**  
**ELK3693**  
 Finishes:  
 (W)

**Sq. Deep Reflector**  
**ELK3318**  
 Finishes:  
 (W, BB, BZ, B, C, H)

**Sq. Adjustable Gimbal**  
**ELK3329**  
 Finishes:  
 (W, BB, BZ, B, C, H)

**Sq. Adjustable Baffle**  
**ELK3393**  
 Finishes:  
 (W)

**Sq. Adjustable Pinhole**  
**ELK3327**  
 Finishes:  
 (B, BB, BZ)

**Square Reflector**  
**ELK3341**  
 Finishes:  
 (W, B, BB, BZ)

\*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring

# Compatible Products




For use with Dedicated 3" IC LED Housings

## 3" Flush Mount Trim Adaptors • For use with ELK36 & ELK33 Trims



**Round Flush Mount**  
EL3FMR



**Square Flush Mount**  
EL3FMS

## 3" LED Light Engines



**Round Baffle**

| CAT NO.       | SPECIFICATIONS             |
|---------------|----------------------------|
| EL311CT3W, BZ | 9W, 700 lm, 2700K - 3500K  |
| EL311CT5W     | 10W, 700 lm, 2700K - 5000K |



**Round Reflector**

| CAT NO.       | SPECIFICATIONS             |
|---------------|----------------------------|
| EL312CT3W, BZ | 9W, 700 lm, 2700K - 3500K  |
| EL312CT5W     | 10W, 710 lm, 2700K - 5000K |



**Round Gimbal**

| CAT NO.   | SPECIFICATIONS             |
|-----------|----------------------------|
| EL313CT3W | 9W, 700 lm, 2700K - 3500K  |
| EL313CT5W | 10W, 700 lm, 2700K - 5000K |



**Square Baffle**

| CAT NO.   | SPECIFICATIONS             |
|-----------|----------------------------|
| EL331CT3W | 12W, 700 lm, 2700K - 3500K |



**Square Reflector**

| CAT NO.       | SPECIFICATIONS            |
|---------------|---------------------------|
| EL33230BZ     | 9W, 640 lm, 3000K         |
| EL332CT3W, BZ | 9W, 700 lm, 2700K - 3500K |




**Pull Down Adjustable**

| CAT NO.            | SPECIFICATIONS       |
|--------------------|----------------------|
| EL39727W, BZ, N    | 10.8W, 800 lm, 2700K |
| EL39730W, B, BZ, N | 10.8W, 800 lm, 3000K |

\*Finishes: **W** - All White, **B** - All Black, **BZ** - All Bronze, **N** - All Nickel

## 3" Accessories



**Emergency Battery Backup**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| KEM-LD5 | 8W, 120/277V   |

\* Requires access from above



**Fire Cover**

| CAT NO. | SPECIFICATIONS      |
|---------|---------------------|
| FIRECVR | 9 3/4" H x 17" O.D. |



**Fire Enclosure**

| CAT NO.    | SPECIFICATIONS                |
|------------|-------------------------------|
| FIREENCL   | 20 3/8" L x 14 3/8" W         |
| FIREENCL-S | Shallow,<br>16" L x 14 3/8" W |



**Mica Fire Tape**

| CAT NO.  | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | 3/4" W x 16' L |