


# 4" 0-10V Remodel Dedicated LED Housing

4" remodel dedicated LED housing. Compatible with 4" 0-10V LED inserts and 0-10V Koto™ Modules.




## Features

- Wired for 0-10V Dimming
- Single wall IC Airtight rated for Direct Contact with Insulation
- 120/277V Input
- Meets restricted air flow requirements (per ASTM E-283)
- cUL Listed for direct contact with Insulation
- cUL Listed for Damp Locations
- cUL Listed for Wet Location with Wet Location Rated Inserts
- cUL Listed for Feed Through
- CA Title 24 Compliant

## Specifications

Voltage	120/277V
Dimmable	0-10V/Triac/ELV
Wet Location	Listed
Damp Location	Listed

## Dimensions



## Technical Details

**Installation:** Designed for ceiling plenums where 2x6 joists or taller joists are used. Maximum hole cutout is 4 1/4". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

**Electrical:** Input Voltage: 120/277V. Inherently protected.

**Dimmability:** Dimmability based on lamp.

**Lamp:** Designed for use with ELCO 4" 0-10V LED inserts and 0-10V Koto™ Module

### Listings:

- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

**Warranty:** ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

## Product Numbers

Item	Description	Voltage	Dimming
EL490RICDXA	4" Remodel	120/277V	0-10V/Triac/ELV
EL490RICDXA-EM	Emergency Battery Backup	120/277V	0-10V/Triac/ELV

# Compatible Products

For use with Dedicated 4" IC LED Housings



## 4" Ply™ 0-10V Dimmable, 120/277V LED Inserts



Round Insert

**EL495**

Finishes:

(DW, DHW, DCW)

### PRODUCT NUMBER BUILDER

4" 120/277V LED Inserts

**EL495**

Color Temperature

**30** 3000K (800 lm)  
**35** 3500K (850 lm)  
**40** 4000K (900 lm)

Finish

**DW** All White  
**DHW** Haze w/White Ring  
**DCW** Chrome w/White Ring



Round Insert with 5-CCT  
and 3-Lumen Switch

**EL475CT5DW**

All White

CAT NO.

EL475CT5DW

COLOR TEMPERATURE

5-CCT Switch  
2700K, 3000K, 3500K,  
4000K, 5000K



LUMENS

3-Lumen Switch  
850 lm, 1000 lm, 1500 lm



## 4" Ply™ 0-10V Dimmable, 120/277V Adjustable LED Inserts



Round Adjustable Gimbal

**EL414**

Finishes:

(DXW, DXB)



Round Adjustable Insert

**EL497**

Finishes:

(DXW, DXB, DXBZ DXN)



Square Adjustable Insert

**EL447**

Finishes:

(DXW, DXB, DXBZ DXN)



### ACCESSORIES

Interchangeable Lens  
(For EL497 & EL447 Series only)

**EP710C** 20° Beam  
**EP712C** 60° Beam

### PRODUCT NUMBER BUILDER

4" 120/277V Adjustable LED Inserts

**EL4**

Style

**14** Adjustable Gimbal  
**97** Round Adjustable  
**47** Square Adjustable

Color Temperature

**27D** 2700K  
**30D** 3000K

Finish


**DXW** All White  
**DXB** All Black  
**DXBZ** All Bronze  
**DXBN** All Nickel

# Compatible Products

For use with Dedicated 4" 0-10V Koto ICAD LED Housings



## 0-10V Koto™ LED Module



0-10V Koto™  
LED Module  
ELK10DX

PRODUCT NUMBER BUILDER				
0-10V Koto™ LED Module	Lumens	Voltage	Color Temperature	Beam Angle
ELK				
	10 1000 lm	DX 120/277V	27 2700K	(blank) 38° lens (Standard)
			30 3000K	-S 18° lens
			35 3500K	-N 25° lens
			40 4000K	-W 60° lens
			SD Sunset Dimming	

### ACCESSORIES



#### Lens

EP731C 18° Lens  
EP732C 25° Lens  
EP733C 38° Lens  
EP734C 60° Lens

\*EP732C, EP733C, EP734C Included



#### Snoot

L50W White  
L50B Black




#### Secondary Optics

L45 Hex Louver  
L46 Linear Lens  
L47 Spread Louver  
L49 Frosted Lens  
L51 Color Shifter

## 4" Pex™ Round Twist-On Trims



Recommended to be  
used with Maximum  
Adjustability Housing




#### Reflector

ELK4118

Finishes:

(W, BB, BZ, B, C, H)



#### Adjustable Gimbal

ELK4129

Finishes:

(W, BB, BZ, B, C, H)




#### Adjustable Pinhole

ELK4127

Finishes:

(B, BB, BZ)



#### Adjustable Baffle

ELK4193

Finishes:

(W, BB, B)



#### Slot Aperture

ELK4130

Finishes:

(W)



#### Rotatable Slot Aperture

ELK4120

Finishes:

(W)



#### Adj. Wall Wash

ELK4122

Finishes:

(W)

# Compatible Products

For use with Dedicated 4" 0-10V Koto ICAD LED Housings




## 4" Pex™ Square Twist-On Trims



**Reflector**

**ELK4218**


Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Gimbal**

**ELK4229**


Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Pinhole**

**ELK4227**

Finishes:  
(B, BB, BZ)



**Adjustable Phenolic Baffle**

**ELK4293**

Finishes:  
(W, BB, B)



**Adj. Slot Rotatable Aperture**

**ELK4220**


Finishes:  
(W)



**Adjustable Wall Wash**

**ELK4222**


Finishes:  
(W)



**Adjustable Reflector**

**ELK4282**

Finishes:  
(W)



**Adjustable Baffle**

**ELK4284**

Finishes:  
(W)

## 4" Flexa™ Twist-On Trims



**Round Reflector**

**ELK4721**


Finishes:  
(WW, BB, BZBZ, BW, CC, CW, HW, CN)



**Round Baffle**

**ELK4723**


Finishes:  
(WW, BB, BZBZ, BW)



**Square Reflector**

**ELK4741**


Finishes:  
(WW, BB, BZBZ, BW, HW)  
*\*Not for Remodel Housing*



**Square Baffle**

**ELK4743**

Finishes:  
(WW, BB, BZBZ, BW)  
*\*Not for Remodel Housing*



**Adjustable Square Reflector**

**ELK4759**

Finishes:  
(WW, BB, B, H)

# Compatible Products




For use with Dedicated 4" 0-10V Koto ICAD LED Housings

## 4" Pex™ Trimless


Only for use with EL485ICDXA & EL490AJICDXA




Round Spackle  
Frame Only  
**EL4SFR**




Round Smooth Reflector  
**ELK408**  
Finishes:  
(W, B, BZ, H)




Round Adjustable  
Reflector  
**ELK415**  
Finishes:  
(W, B, BZ, H)




Adjustable Reflector  
with Spackle Frame  
**ELK430**  
Finishes:  
(W, B, BZ, H)




Adjustable Baffle  
with Spackle Frame  
**ELK434**  
Finishes:  
(W, B, BZ)



Sq. Spackle Frame  
**EL4SFS**




Sq. Smooth Reflector  
**ELK445**  
Finishes:  
(W, B, H)




Sq. Adjustable Reflector  
**ELK459**  
Finishes:  
(W, B, H)

## 4" Flush Mount Trim Adaptors




Round Flush Mount  
**EL4FMR**  
For use with  
ELK41 & Unique™ Trims



Square Flush Mount  
**EL4FMS**  
For use with  
ELK42 Trims

## 4" Accessories



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V

\* Requires access from above




Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L