

4" 120/277/347V LED Recessed Gimbal Downlight with 5-CCT Switch

Our 4" Dimmable LED Recessed Gimbal Downlight is designed for quick and easy installation without a housing for both new construction and remodel applications, giving you the options you are looking for in one fixture. The manual switch allows you to choose between 2700K, 3000K, 3500K, 4000K or 5000K. IC-Rated for use with direct contact with insulation.




Features

- Adjustable Gimbal offers 25° tilt range
- IC Airtight for use with direct contact to insulation.
- Lumens (Wattage): 650 lm (10W)
- Designed to fit in plenums as shallow as 3".
- Eliminates the need for housing.
- New Construction application requires mounting plate or frame.
- Remodel applications require no additional accessories.
- Wet Location allows for use indoors or outdoors.
- ETL listed
- Includes driver and Jbox.

Specifications

| | |
|----------------------|-----------------------------------|
| Wattage | 10W |
| Lumens | 650 lm |
| Voltage | 120/277/347V |
| Color Temp. | 2700K, 3000K, 3500K, 4000K, 5000K |
| Dimmable | 0-10V/Triac/ELV |
| Lamp Type | LED |
| CRI | 90+ |
| Damp Location | Listed |

Dimensions



Technical Details

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: IC-rated driver and fixture are tested and approved for direct contact with insulation. Plenum-rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High-strength steel spring clip for easy installation. Maximum hole size should not exceed 4 1/2" for this product. Suitable installation for t-grid and drop ceiling applications.

Electrical: Driver connects directly to 120/277/347V power supply. Standard input wattage is 10W, 65 lumens per watt.

Dimmability: Works with 120/277/347V dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatibility List.

Listings: ETL Listed for Wet Locations. IC-Rated for direct contact with insulation.

Warranty: 5-year limited warranty.

Product Numbers

| Item | Lamp type | Lumens | CCT | Watts | Voltage | Dimming | Finish |
|--------------|-----------|--------|--------|-------|--------------|-----------------|-----------|
| ERT413CT5DXW | LED | 650 lm | 2700K, | 10W | 120/277/347V | 0-10V/Triac/ELV | All White |
| | | | 3000K, | | | | |
| | | | 3500K, | | | | |
| | | | 4000K, | | | | |
| | | | 5000K | | | | |