

Project name:	
Fixture type:	
Date:	

4" Airtight Remodel IC Housing with GU24 Base Socket




Features

- Airtight Remodel Housing for insulated ceilings.
- Adjustable socket bracket.
- Four remodel clips secure housing and accommodate various ceiling thickness.
- Adjustable socket bracket allows for different lamp types/sizes and proper and consistent lamp positioning.
- Pre-wired junction box provided with 1/2" and 3/4" knockouts and with removable access plates.
- Trims sold separately.
- Lamp: LED Insert or 18W MAX. Self ballasted 120V CFL, GU24 base.
- Meets California Title 24 requirements with LED insert only.
- cUL Listed for damp location and for feed through.

Specifications

Wattage	18W			
Voltage	120V			
Lamp Type	Medium Base (E26)			
Damp Location Listed				

Dimensions



Product Number

Item	Lamp type	Watts	Voltage
EL99RICA-G24	Medium Base (E26)	18W	120V

Technical Details

Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- · Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. Maximum hole cutout is 4 1/4". See installation sheet for detailed information.

Electrical:

- Input Voltage: 120V AC.
- · Thermally protected against improper lamping.

Trims: Compatible with ELCO 4" Line Voltage PAR trims.

Lamp: Designed for use with Medium Base (E26) PAR lamps up to 50W.

Listings

- · cUL Listed for Damp Location.
- · cUL Listed for Feed Through.
- cull Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.