

Project name:		
Fixture type:		
Date:		

# 4" Baffle Trim



## **Features**

- Baffle Trim.
- Includes field changeable 3-optic lens (14°, 24°, 36°).
- O.D.: 4 7/8".

# **Specifications**

**Beam Angle** 14°, 24°, 36°

# **Product Numbers**

Item	Beam Angle	Finish
EL4493W	14°, 24°, 36°	All White

# **Technical Details**

#### Construction:

- Meticulously manufactured trim with powder coated or anodized finish.
- Diecast trim ring for durability and lasting quality.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into housing and keeps ring flush with ceiling.

Housings: Compatible with ELD46ICA, ELDR46ICA.

# **Compatible** Products




# 4" Integrated LED Housings











## **IC Airtight New Construction Housing**

	3	<b>3</b>		
•	CAT NO.	SPECIFICATIONS		
-	ELD47ICA	1200 lm/ 16W / 2700K		
ı	ELD46ICA	1200 lm/ 16W / 3000K		
1	ELD45ICA	1200 lm/ 16W / 4000K		



## IC Airtight Remodel Housing

CAT NO.	SPECIFICATIONS
ELDR47ICA	1200 lm/ 16W / 2700K
ELDR46ICA	1200 lm/ 16W / 3000K
ELD45ICA	1200 lm/ 16W / 4000K