
ELCO Lighting

Project name:

Fixture type:

Date:

4" Cedar System New Construction IC Airtight Housing w/Driver



Double Wall IC Airtight housing for high-end residential and light commercial, 1250 lumen.

Features

- cUL Listed for direct contact with insulation.
- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- Flicker-Free Dimming.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 4" LED Light Engines.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Lumens	1250 lm - 1600 lm
Voltage	120/277V or 120V
Dimmable	Triac/ELV, Triac/ELV/0-10V, Sunset
Power Factor	≥0.95
Damp Location	Listed

Technical Details

Construction:

- Double wall IC rated for direct contact with insulation. For use in IC and non-IC conditions. Up to 1600 lumens.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

Installation:

- Designed for ceiling plenums where 2x6 joists or taller are used.
- High strength hanger bars can easily be nailed to joists.
- Suitable for T-grid and drop ceiling applications.
- See installation sheet for detailed information.
- Emergency Battery Back-up Option requires access from above.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4” knockouts, Seven 1/2” trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Hanger Bars: Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.95.

Emergency Battery Pack: Optional 90 minute battery pack available with test indicator switch. Note that double wall housings require Access From Above Ceiling for Battery Maintenance.

Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 5% with a compatible dimmer.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.


Listings: cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Direct Contact with Insulation and Combustible Material. cUL Listed for Feed Through.

Options




Optional Butterfly Bracket

E4LC12



E4LC16



Product Numbers

Item	Lumens	Voltage	Dimming
E4LC12ICA2	1250 lm	120V	Triac/ELV
E4LC12ICAD2	1250 lm	120/277V	Triac/ELV/0-10V

© ELCO Lighting 2024. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Item	Lumens	Voltage	Dimming
E4LC12ICASD	1250 lm	120/277V	Sunset
E4LC16ICA2	1600 lm	120V	Triac/ELV
E4LC16ICAD2	1600 lm	120/277V	Triac/ELV/0-10V
E4LC16ICASD	1600 lm	120/277V	Sunset

Product Number Builder Example: **E4LC12ICA2**

ELCO Cedar 4" Housing	Lumens	IC Airtight	Dimming	Generation	Optional
E4LC	**12** 1250 lm **16** 1600 lm	**ICA** ICA	120V Triac/ELV **D** Triac/ELV/0-10V **SD** Sunset **L** Lutron	**2** Gen 2 Gen 1	No EM **EM1** Emer. Backup up to 700 lm **EM2** Emer. Backup to 1100 lm

© ELCO Lighting 2024. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4″ Cedar™ IC LED housings**

4″ Cedar™ LED Light Engines



Round Reflector Trim
E410C
Finishes:
(W, B, C, H, BZ, BB, MW, MB)



Wall Wash Reflector Trim
E411C
Finishes:
(W, B, C, H, BZ, BB, MW, MB)



Drop Glass Reflector Trim
E412C
Finishes:
(W, B, C, H, BB, MW, MB)



Round Baffle Trim
E414C
Finishes:
(W, B, BZ, BB)



Round Pinhole Trim
E429C
Finishes:
(W, B, C)



Square on Sq. Baffle Trim
E415C
Finishes:
(W, BZ)



Square on Sq. Reflector Trim
E417C
Finishes:
(W, BZ)



Round on Sq. Reflector Trim
E420C
Finishes:
(W, C, H, BZ, BB)



Round on Sq. Baffle Trim
E424C
Finishes:
(W, B, BZ, BB)



Round Adjustable Trim
E418C
Finishes:
(W, C, BB, BZ)



Square Adjustable Trim
E428C
Finishes:
(W, C, BB, BZ)

PRODUCT NUMBER BUILDER

4″ Cedar™ Trim	Style	Lumen	Color Temperature	Finish
E4				
	10C Reflector	**12** 1250 lm (12.88W)	**27** 2700K	**W** All White
	11C Wall Wash	**16** 1600 lm (18W)	**30** 3000K	**B** Black w/White Ring
	12C Drop Glass		**35** 3500K	**BZ** All Bronze
	14C Baffle		**40** 4000K	**BB** All Black
	15C Sq. on Sq. Baffle		**50** 5000K	**C** Chrome w/White Ring
	17C Sq. on Sq. Reflector		**SD** Sunset Dimming	**H** Haze w/White Ring
	18C Round Adjustable			**MW** Matte White
	20C Round on Sq. Reflector			**MB** Matte Black
	24C Round on Sq. Baffle			
	28C Square Adjustable			

© ELCO Lighting 2024. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products


For use with **4" Cedar™ IC LED housings**

4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 ⅜" L x 14 ⅜" W
FIREENCL-S	Shallow, 16" L x 14 ⅜" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W x 16' L

© ELCO Lighting 2024. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.