

4" Cedar System Non-IC New Construction Housing w/ Driver

Non-IC Airtight housing for high-end residential and light commercial, 1600 lumens.




Features

- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Cedar™ System 4" LED Light Engines.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Lumens	1600 lm
Voltage	120/277V or 120V
Dimmable	Triac/ELV, Triac/ELV/0-10V, Sunset

Dimensions



Technical Details

Construction: Non-IC Frame for non-IC conditions. Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.

Installation: Designed for ceiling plenums where 2x6 joists or taller are used. High strength hanger bars can easily be nailed to joists. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

Hanger Bars: Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Electrical: Driver is rated for 120V and 277V input (120/277V). High Efficiency driver with a power factor > 0.95.

Dimmability: 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver. 0-10V dimming down to 5% with a compatible dimmer. Can be specified with Lutron drivers for 0.1% and 1% dimming. For a full list of dimmers refer to the Dimmer Compatibility List.

Emergency Battery Pack: Optional 90 minute battery pack available with test indicator switch. Note that double wall housings require Access From Above Ceiling for Battery Maintenance.

Listings: UL Listed for Damp Location and for Wet Location with select trims. UL Listed for Feed Through.

Product Numbers

Item	Lumens	Voltage	Dimming
E4LC162	1600 lm	120V	Triac/ELV
E4LC16D2	1600 lm	120/277V	Triac/ELV/0-10V
E4LC16SD	1600 lm	120/277V	Sunset

Product Number Builder Example: E4LC162

ELCO Cedar 4" Housing	Lumens	IC Airtight	Dimming	Generation
E4LC	16 1600 lm	ICA ICA	(Blank) 120V Triac/ELV D 120/277V Triac/ELV/0-10V SD Sunset L Lutron	Gen 1 2 Gen 2
Optional				

(blank) No Emergency Battery

EM1 Em. battery up to 700 lm

EM2 Em. battery up to 1100 lm

Compatible Products



For use with 4" Cedar™ Non-IC LED housings

4" Cedar™ LED Light Engines



Round Reflector Trim

E410C

Finishes:
(W, B, C, H, BZ, BB, MW, MB)



Wall Wash Reflector Trim

E411C

Finishes:
(W, B, C, H, BZ, BB, MW, MB)



Drop Glass Reflector Trim

E412C

Finishes:
(W, B, C, H, BB, MW, MB)



Round Baffle Trim

E414C

Finishes:
(W, B, BZ, BB)



Round Pinhole Trim

E429C

Finishes:
(W, B, C)



Square on Sq. Baffle Trim

E415C

Finishes:
(W, BZ)



Square on Sq. Reflector Trim

E417C

Finishes:
(W, BZ)



Round on Sq. Reflector Trim

E420C

Finishes:
(W, C, H, BZ, BB)



Round on Sq. Baffle Trim

E424C

Finishes:
(W, B, BZ, BB)



Round Adjustable Trim

E418C

Finishes:
(W, C, BB, BZ)



Square Adjustable Trim

E428C

Finishes:
(W, C, BB, BZ)

PRODUCT NUMBER BUILDER

4" Cedar™ Trim	Style	Lumen	Color Temperature	Finish
E4				
	10C Reflector	16 1600 lm (18W)	27 2700K	W All White
	11C Wall Wash		30 3000K	B Black w/White Ring
	12C Drop Glass		35 3500K	BZ All Bronze
	14C Baffle		40 4000K	BB All Black
	15C Sq. on Sq. Baffle		50 5000K	C Chrome w/White Ring
	17C Sq. on Sq. Reflector		SD Sunset Dimming	H Haze w/White Ring
	18C Round Adjustable			MW Matte White
	20C Round on Sq. Reflector			MB Matte Black
	24C Round on Sq. Baffle			
	28C Square Adjustable			

Compatible Products

For use with 4" Cedar™ Non-IC LED housings



4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L