

# 4" Chrome Reflector with Suspended Frosted Glass



## Features

- Reflector with Suspended Frosted Glass.
- Lamp: 32W MAX CFL (PL-T) or 50W MAX PAR20, R20.
- O.D.: 4 7/8".

## Technical Details

**Construction:** Meticulously manufactured trim with a powder coated or anodized finish.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 4" Line Voltage IC and Non-IC versions.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Options



**Bronze**



**Black**



**White**

## Product Numbers

Item	Finish
EL926W	All White
EL926B	All Black
EL926BZ	All Bronze

## Product Number Builder Example: EL926W

4" Reflector with Suspended Frosted Glass

Finish

**EL926**

- B** All Black
- W** All White
- BZ** All Bronze

# Compatible Products

For use with 4" Trims for PAR Lamps

## 4" Line Voltage ICA Housings



4" Airtight IC Housing  
**Double Wall Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

## 4" Accessories



**Fire Cover**

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



**Fire Enclosure**

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



**Mica Fire Tape**

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L