

# 4" LED IC Airtight Sloped Ceiling Remodel Housing

ELCO Slant allows for installation in sloped ceilings ranging from 2/12 (10°) to 6/12 (26.5°). Can be used in insulated ceilings. Fits in 2" x 8" joist construction.




## Features

- Allows for direct contact with insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- California Title 24 (JA8-2016-E).

## Specifications

<b>Wattage</b>	14W
<b>Voltage</b>	120V
<b>Damp Location</b>	Listed

## Dimensions



## Technical Details

### Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Housing adjusts to accommodate up to 3/4" ceiling thickness.
- Aluminum housing for greater heat dissipation.

**Installation:** Designed for ceiling plenums where 2x8 joists or taller are used. Template for hole cutout is provided with each housing. See installation sheet for detailed information.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and One 3/4" knockout. Four true pry-out knockout slots for easy Romex installation.

**Electrical:** Connection is rated for 120V input.

**Compatible Housings:** EL470ICA, EL470RICA.

### Listings:

- cUL Listed for Damp Location.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- cUL Listed for Feed Through.
- AirTight Per ASTM E-283.
- California Title 24 (JA8-2016-E).

**Warranty:** ELCO Products are built to last. 5-year Limited warranty.

## Product Numbers

Item	Watts	Voltage
EL470RICA	14W	120V

# Compatible Products

For use with 4" Dedicated LED Sloped Ceiling IC Housings

## 4" LED Sloped Inserts



4" LED Sloped Insert  
Baffle Trim




4" LED Sloped Insert  
Reflector Trim

CAT NO.	SPECIFICATIONS
EL423CT5W	White, 900 lm, 2700K-5000K
EL423CT5BZ	Bronze, 900 lm, 2700K-5000K

CAT NO.	SPECIFICATIONS
EL425CT5W	White, 900 lm, 2700K-5000K

## Koto™ LED Module & Sloped Trim



Koto™ LED  
Module  
& Sloped Trim

PRODUCT NUMBER BUILDER						
Koto™ LED Module	Lumens	Color Temperature	-	4" Round Pex™ Sloped Trim	Finish	
ELK						
07	770 - 860 lm	27	2700K	-	ELK4357 Reflector	W All White
09	940 - 1100 lm	30	3000K		ELK4347 Reflector with Clear Glass	BB All Black
11	1050 - 1260 lm	35	3500K		ELK4349 Reflector with Frosted Lens	BZ All Bronze
08 (CT5)	825 lm	40	4000K			B Black/White Ring
10 (CT5)	1000 lm	SD	Sunset (For ELK09 & ELK11)			H Haze/White Ring
13	1250 - 1400 lm	CT5	2700K - 5000K			
		HC	Human Centric (For ELK11 Only)			