

4" LED IC Airtight Sloped Ceiling Remodel Housing

ELCO Slant allows for installation in sloped ceilings ranging from 2/12 (10°) to 6/12 (26.5°). Can be used in insulated ceilings. Fits in 2" x 8" joist construction.




Features

- Allows for direct contact with insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- California Title 24 (JA8-2016-E).

Specifications

Wattage	14W
Voltage	120V
Damp Location	Listed

Dimensions



Technical Details

Construction:

- IC Rated for Direct Contact with Insulation.
- Designed for use in 2/12 to 6/12 sloped ceiling.
- Housing adjusts to accommodate up to 3/4" ceiling thickness.
- Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x8 joists or taller are used. Template for hole cutout is provided with each housing. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and One 3/4" knockout. Four true pry-out knockout slots for easy Romex installation.

Electrical: Connection is rated for 120V input.

Compatible Housings: EL470ICA, EL470RICA.

Listings:

- cUL Listed for Damp Location.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- cUL Listed for Feed Through.
- AirTight Per ASTM E-283.
- California Title 24 (JA8-2016-E).

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Product Number

Item	Watts	Voltage
EL470RICA	14W	120V

Compatible Products

For use with 4" Dedicated LED Sloped Ceiling IC Housings

4" LED Sloped Inserts



4" LED Sloped Insert
Baffle Trim




4" LED Sloped Insert
Reflector Trim

CAT NO.	SPECIFICATIONS
EL423CT5W	White, 900 lm, 2700K-5000K
EL423CT5BZ	Bronze, 900 lm, 2700K-5000K

CAT NO.	SPECIFICATIONS
EL425CT5W	White, 900 lm, 2700K-5000K

Koto™ LED Module & Sloped Trim



Koto™ LED
Module
& Sloped Trim

PRODUCT NUMBER BUILDER						
Koto™ LED Module	Lumens	Color Temperature	-	4" Round Pex™ Sloped Trim	Finish	
ELK						
07	770 - 860 lm	27	2700K	-	ELK4357 Reflector	W All White
09	940 - 1100 lm	30	3000K		ELK4347 Reflector with Clear Glass	BB All Black
11	1050 - 1260 lm	35	3500K		ELK4349 Reflector with Frosted Lens	BZ All Bronze
08 (CT5)	825 lm	40	4000K			B Black/White Ring
10 (CT5)	1000 lm	SD	Sunset (For ELK09 & ELK11)			H Haze/White Ring
13	1250 - 1400 lm	CT5	2700K - 5000K			
		HC	Human Centric (For ELK11 Only)			