ELCO Lighting

Project name:

Fixture type:

Date:

# 4" LED Light Engine with Drop Glass Reflector Trim

The perfect lighting solution for high-end residential and light commercial projects.

## Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Must be used with ELCO 4" Cedar™ System Housings.
- Frosted acrylic module lens for even lumen distribution.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

## Specifications

| | |
|---|---|
| **Wattage** | 18W |
| **Lumens** | 1600 lm |
| **Color Temp.** | 2700K |
| **Lamp Type** | LED |
| **Beam Angle** | 60° |
| **CRI** | 93+ |
| **Damp Location** | Listed |

## Technical Details

**Optics**: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Trim Construction**: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

**Installation:** Must be installed on a Cedar™ System housing with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.

**LED Technology:**

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

**Sunset:** Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

**Listings**: cUL Listed for Wet Location. RoHS Compliant.

## Options

**Black w/White Trim**

**All Bronze**

**Chrome w/White Trim**

**Chrome w/Nickel Trim**

**Haze w/White Trim**

**All White**

**All Black**

## Dimensions

© ELCO Lighting 2025. All rights reserved • Rev. 25 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

## Product Number Builder

Example: **E412C0827W2**

| ELCO 4" Drop Glass Reflector | Lumens | Color Temp. | Finish | Generation | Beam Angle |
|---|---|---|---|---|---|
| **E412C** | **08** 850 lm | **27** 2700K | **W** All White | **2** Gen 2 | 60º lens |
| | **12** 1250 lm | **30** 3000K | **BB** All Black | **1** Gen 1 | **-F** 38º lens |
| | **16** 1600 lm | **35** 3500K | **BZ** All Bronze | | **-N** 24º lens |
| | | **40** 4000K | **B** Black with White Trim | | **-S** 15º lens |
| | | **50** 5000K | **C** Chrome with White Trim | | |
| | | **SD** Sunset [1] | **H** Haze with White Trim | | |

[1] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed


© ELCO Lighting 2025. All rights reserved • Rev. 25 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

# Compatible Products

For use with **4″ Cedar™ Light Engines**

## 4″ Cedar™ Dedicated LED ICA Housings

2-Hour Fire Rated
4″ ICA Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4FH | Up to 850 lm |

4″ ICA Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LC | Up to 1600 lm |

4″ ICA Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LC | Up to 850 lm |

4″ ICA Housing
**Remodel**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LRC | Up to 850 lm |

## 4″ Cedar™ Dedicated LED Non-IC Housings

4″ Non-IC Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LC | Up to 1600 lm |

4″ Non-IC Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LC | Up to 1250 lm |

4″ Non-IC Housing
**Remodel**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LRC | Up to 1250 lm |

### PRODUCT NUMBER BUILDER

| Housing Type | | Lumen | | Optional | | Dimming | |
|---|---|---|---|---|---|---|---|
| **E4FH** | Fire Rated (up to 850) | **08** | 850 lm (8.76W) | **(Blank)** | Non-IC | **(Blank)** | 120V Triac/ELV |
| **E4LC** | New Construction | **12** | 1250 lm (12.88W) | **ICA** | IC Airtight | **D** | 120/277V Triac/ELV/0-10V |
| **E4LRC** | Remodel | **16** | 1600 lm (18W) | | | **SD** | Sunset |
| | | | | | | **L** | Lutron |

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2025. All rights reserved • Rev. 25 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.