

4" LED Sloped Round Regressed Gimbal with 5-CCT Switch

Our 4" LED Sloped Regressed Gimbal Downlight is designed for quick and easy installation without a housing for both new construction and remodel applications, gives you the options you are looking for in one fixture. The manual switch allows you to choose between 2700K, 3000K, 3500K, 4000K or 5000K. IC-Rated for use with direct contact with insulation.




Features

- Adjustable Regressed Gimbal for Wall Wash and Sloped Ceiling
- 38° beam with 25° tilt and 360° rotation
- IC Airtight for use with direct contact to insulation
- Designed to fit in plenums as shallow as 3".
- Eliminates the need for housing.
- New Construction application requires mounting plate or frame.
- Remodel applications require no additional accessories.
- Wet Location for indoor use only.
- ETL listed, Energy Star, Title 24 JA8
- Includes driver and Jbox.

Specifications

| | |
|---------------------|-----------------------------------|
| Wattage | 8W |
| Lumens | 510 lm |
| Voltage | 120V |
| Color Temp. | 2700K, 3000K, 3500K, 4000K, 5000K |
| Dimmable | Triac/ELV |
| Lamp Type | LED |
| Beam Angle | 38° |
| CRI | 90+ |
| Wet Location | Listed |

Dimensions



Technical Details

Construction: IC rated driver and fixture are tested and approved for direct contact with insulation. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation. Maximum hole size should not exceed 4 3/4" for this product. Suitable installation for t-grid and drop ceiling applications.

Electrical: Standard input wattage is 8W, 63.75 lumens per watt.

Dimmability: Works with 120V Triac/ELV type dimmers. For full list of dimmers, refer to the Dimmer Compatibility List.

Listings: ETL Listed for Wet Locations. IC-Rated for direct contact with insulation.

Warranty: 5-year limited warranty.

Product Numbers

| Item | Lamp type | Lumens | CCT | Watts | Voltage | Dimming | Beam Angle | Finish |
|------------|-----------|--------|--------|-------|---------|-----------|------------|--------|
| ERT425CT5W | LED | 510 lm | 2700K, | 8W | 120V | Triac/ELV | 38° | White |
| | | | 3000K, | | | | | |
| | | | 3500K, | | | | | |
| | | | 4000K, | | | | | |
| | | | 5000K | | | | | |