

| Project name: | |
|---------------|--|
| Fixture type: | |
| Date: | |

4" Metal Step Baffle Trim with Lamp Holder Bracket



Features

- Baffle Trim.
- Integral Socket Bracket to control lamp height.
- Lamp: 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options







White

Black w/White Trim

Nickel







Bronze

Black w/Nickel TrimNickel w/Black Trim



Nickel w/White Trim

Product Numbers

| Item | Finish |
|----------|------------------------|
| EL993KW | All White |
| EL993KB | Black with White Trim |
| EL993KN | Nickel |
| EL993KBZ | All Bronze |
| EL993KBN | Black with Nickel Trim |
| EL993KNB | Nickel with Black Trim |
| EL993KNW | Nickel with White Trim |
| | |

Product Number Builder Example: EL993KW

| 4" Baffle Trim with Socket Bracket | Socket Bracket | | Finish |
|------------------------------------|-------------------------|----|------------------------|
| EL993 | | | |
| | no Socket Bracket | w | All White |
| | K Socket Bracket | В | Black w/White Ring |
| | | N | All Nickel |
| | | ΒZ | All Bronze |
| | | BN | Black with Nickel Trim |
| | | NB | Nickel with Black Trim |
| | | NW | Nickel with White Trim |

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing New Construction




4" Airtight IC Housing New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99ICA | Lamp: 50W MAX. |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99A | Lamp: 50W MAX. |

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------|
| EL99LDICA | Lamp: LED 12W MAX. |



4" Airtight IC Housing with GU24 Base Socket New Construction



4" Airtight IC 2-Hour Fire Rated Housing

New Construction

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| EL99ICA-G24 | Lamp: 18W MAX. |

| CAT NO. | SPECIFICATIONS | |
|----------|----------------|--|
| EL99FICA | Lamp: 35W MAX. | |

4" Accessories



Fire Cover

Fire Enclosure



Mica Fire Tape

| CAT NO. | SPECIFICATIONS |
|---------|-------------------|
| FIRECVR | 9 ¾" H x 17" O.D. |

| CAT NO. | SPECIFICATIONS |
|------------|--------------------------|
| FIREENCL | 20 3/8" L x 14 3/8" W |
| FIREENCL-S | Shallow, 16" L x 14 %" V |

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | ¾" W × 16' L |