

# 4" Phenolic Step Baffle Trim



## Features

- Phenolic Step, Metal Ring.
- Lamp: 32W MAX CFL (PL-T) or 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

## Technical Details

### Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 4" Line Voltage IC and Non-IC versions.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Options




All White



Black w/White Trim



All Bronze



All Nickel



All Black



Nickel w/White Trim

## Product Numbers

Item	Finish
EL993B	Black with White Trim
EL993BZ	All Bronze
EL993W	All White
EL993N	All Nickel
EL993BB	All Black
EL993NW	Nickel with White Trim

## Product Number Builder Example: EL993B

4" Phenolic Baffle Metal Trim

Finish

**EL993**

- B** Black with White Trim
- BZ** All Bronze
- W** All White
- BB** All Black
- NW** Nickel with White Trim

# Compatible Products

For use with 4" Trims for PAR Lamps

## 4" Line Voltage ICA Housings



4" Airtight IC Housing  
**Double Wall Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

## 4" Accessories



**Fire Cover**

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



**Fire Enclosure**

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



**Mica Fire Tape**

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L