

Project name:		
Fixture type:		
Date:		

## 4" Phenolic Step Baffle Trim



#### **Features**

- Phenolic Step, Metal Ring.
- Lamp: 40W A19 or R16, 50W PAR20 or R20
- O.D.: 4 3/4".

#### **Technical Details**

#### **Construction:**

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



#### **Product Number**

Item	Finish
EL993WN	White with Nickel Trim

4" Phenolic Baffle Metal Trim	Finish
EL993	
w	All White
В	Black with White Trim
N	All Nickel
ВІ	B All Black
BZ	Z. All Bronze
ВІ	Black with Nickel Trim
N	Nickel with Black Trim
W	N White with Nickel Trim
N	V Nickel with White Trim
ВІ	Z Black with Bronze Trim
BZ	W Bronze with White Trim
w	BZ White with Bronze Trim

# **Compatible** Products



For use with 4" Trims for PAR Lamps

## 4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction** 



4" Airtight Housing **New Construction** 



4" Airtight IC Housing **New Construction** 

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
FL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction** 



4" Airtight IC 2-Hour Fire Rated Housing **New Construction** 

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

### 4" Accessories

CAT NO.

**FIRECVR** 



Fire Cover

SPECIFICATIONS

9 ¾" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 %" L x 14 %" W
FIREENCL-S	Shallow, 16" L x 14 %" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS	
FIRETAPE	³⁄4" W × 16' L	