

Project name:	
Fixture type:	
Date:	

## 4" Phenolic Step Baffle Trim



#### **Features**

- Phenolic Step, Metal Ring.
- Lamp: 32W MAX CFL (PL-T) or 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

#### **Technical Details**

#### Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



Finish

White with Nickel Trim

EL993WN

4" Phenolic Baffle Metal Trim		Finish
EL993		
	В	Black with White Trim
	BZ	All Bronze
	W	All White
	N	All Nickel
	ВВ	All Black
	BN	Black with Nickel Trim
	WN	White with Nickel Trim
	NW	Nickel with White Trim
	BBZ	Black with Bronze Trim
	BZW	Bronze with White Trim
	WBZ	White with Bronze Trim

# **Compatible** Products



For use with 4" Trims for PAR Lamps

## 4" Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction** 



4" Airtight Housing **New Construction** 



4" Airtight IC Housing **New Construction** 

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO. **SPECIFICATIONS** EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction** 



4" Airtight IC 2-Hour Fire Rated Housing **New Construction** 

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

### 4" Accessories

CAT NO.

**FIRECVR** 



Fire Cover

SPECIFICATIONS

9 3/4" H x 17" O.D.





Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 ¾" L x 14 ¾" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3⁄4" W × 16' L