

4" Ply Sylo™ Surface Mount

This unique Ply Sylo™ LED Surface Mount gives you the options you are looking for. Engineered with energy-efficient LED technology and dimming options for your project.



Features

- Modern Surface Mount Die-Cast aluminum fixture for easy maintenance and upgrades
- Integral EM option 15W Max, for over 15W use EJB4ICA-EM5 external EM and housing
- Fits 3 ½" and 4" Octagon and Round Junction boxes
- Manual switch to choose desired Color Temperature and Lumen Output
- 120V Triac/ELV dimming or 120/277V 0-10V dimming options available
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- 90+ CRI for extremely accurate color rendering
- CA Title 24, ETL listed, ENERGY STAR, JA8-2022-E
- Life span of 50,000 hours L70

Specifications

Wattage	15 MAX.W
Lumens	1000 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Wet Location	Listed

Options



All White



All Black



Haze with White Trim



Integral EM Switch

Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED Array technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat sink allows for efficient cooling. High quality powder coat finish preventing rust and paint cracking.

Installation: Included bracket mounts to 3 ½" and 4" Octagon and Round Junction boxes.

Electrical: Specifiable in 120V or 120/277V input. High Efficiency driver with a power factor > 0.9. Start time of less than .75 seconds.

Emergency Battery Backup: Integral EM Test Switch on Cylinder. The fixture becomes 120V only. Integral EM option 15W Max, for over 15W use EJB4ICA-EM5 external EM and housing


LED Technology: Extremely accurate Color Rendering Index of 90+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Dimmability: Optional Triac/ELV or 0-10V dimming. For full list of dimmers, refer to the Dimmer Compatibility List. Industry-leading dimming that dims smoothly with no hot spots or flickering.

Listings: cUL Listed for Wet Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2019 standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Dimensions



Product Number

Item	Description	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ESF42710CT5HWEM	Emergency Battery Backup	LED	1000 lm	2700K, 3000K, 3500K, 4000K, 5000K	15 MAX.	120V	Triac/ELV	Haze with White Ring

Product Number Builder

Example: **ESF427L3CT5W**

4" Ply Sylo™ Surface Mount

ESF4

Dimming

27 120V, Triac/ELV ^{1,2}
75 120/277V, 0-10V ^{3,4}

Lumen Output (Wattage)

L3 up to 1500 lm (18W MAX.) ^{5,6}
10 1000 lumen (15W) ^{7,8}

Color Temp.

CT5 2700K-5000K ⁹

Color Finish

W All White
BB All Black ¹⁰
HW White with Haze Reflector

Optional

EM No Emergency Battery
Em. battery 15W MAX. ¹¹

¹ Only available as 120V input

² Lumen Switch: 1000/1250/1500 lm (12.5/16/18W)

³ Only available as 120/277V input

⁴ Lumen Switch: 850/1000/1500 lm (9.5/13.5/18W)

⁵ Lumen Switch located on module

⁶ With 0-10V Lumen Switch: 850/1000/1500 lm, with 0-Triac/ELV Lumen Switch: 1000/1250/1500 lm

⁷ Only available as Triac/ELV

⁸ Only available in White and Haze

⁹ Color Temperature Switch located on module

¹⁰ Only for L3 Option

¹¹ The fixture becomes 120V only