

4" Reflector Trim



Features

- Reflector Trim.
- Lamp: 32W max CFL (PL-T), 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 5"

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4" Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options



All White



Clear w/White Trim



All Bronze



Haze w/White Trim



All Gold



Black w/White Trim




All Black



Clear w/Nickel Trim

Dimensions



Product Numbers

Item	Finish
EL999BZ	All Bronze
EL999W	All White

Item	Finish
EL999B	Black with White Trim
EL999C	Clear with White Trim
EL999H	Haze with White Trim
EL999BB	All Black
EL999CN	Clear with Nickel Trim
EL999GG	All Gold

Product Number Builder Example: **EL999BZ**

4" Reflector Trim

Finish

EL999

- BZ** All Bronze
- W** All White
- B** Black with White Trim
- C** Clear with White Trim
- H** Haze with White Trim
- BB** All Black
- CN** Clear with Nickel Trim
- GG** All Gold

Compatible Products

For use with 4" Trims for PAR Lamps

4" Line Voltage ICA Housings



4" Airtight IC Housing
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L