

Project r	name:		
Fixture t	ype:		
Date:			

4" Reflector Trim with Socket Bracket



Features

- · Reflector Trim.
- Integral Socket Bracket to control lamp height.
- Lamp: 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 5"

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options







All White

Black/White Trim

Clear/White Trim



Gold/White Trim

Dimensions



Product Numbers

Item	Finish
EL999KW	All White
EL999KB	Black with White Trim
EL999KC	Clear with White Trim
EL999KG	Gold with White Trim

Product Number Builder Example: EL999KW

4" Reflector Trim	Finish
EL999K	
	W All White
	B Black with White Trim
	C Clear with White Trim
	G Gold with White Trim

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**



4" Airtight IC Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction**



4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories





Fire Enclosure

	-
1	- >//

Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" \

CAT NO.	SPECIFICATIONS
FIRETAPE	3⁄4" W × 16' L