

# 4" Reflector Trim



## Features

- Reflector Trim.
- Lamp: 32W max CFL (PL-T), 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 5"

## Technical Details

**Construction:** Meticulously manufactured trim with a powder coated or anodized finish.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 4" Line Voltage IC and Non-IC versions.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Options



All White



Clear w/White Trim



All Bronze



Haze w/White Trim



All Gold



Black w/White Trim




All Black



Clear w/Nickel Trim

## Dimensions



## Product Number

Item	Finish
EL999C	Clear with White Trim

**Product Number Builder** Example: **EL999BZ**

---

4" Reflector Trim

Finish

**EL999**

- BZ** All Bronze
- W** All White
- B** Black with White Trim
- C** Clear with White Trim
- H** Haze with White Trim
- BB** All Black
- CN** Clear with Nickel Trim
- GG** All Gold

# Compatible Products

For use with 4" Trims for PAR Lamps

## 4" Line Voltage ICA Housings



4" Airtight IC Housing  
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket  
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing  
New Construction


CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

## 4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L