

| Project name: | |
|---------------|--|
| Fixture type: | |

4" Reflector Trim



Features

- · Reflector Trim.
- Lamp: 32W max CFL (PL-T), 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 5"

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options

Date:







All White

Clear w/White Trim

All Bronze







Haze w/White Trim

All Gold

Black w/White Trim






All Black

Clear w/Nickel Trim

Dimensions



Product Number

| Item | Finish |
|--------|----------------------|
| EL999H | Haze with White Trim |

4" Reflector Trim

Finish

BZ All Bronze

W All White
B Black with White Trim
C Clear with White Trim
H Haze with White Trim
BB All Black
CN Clear with Nickel Trim
GG All Gold

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**




4" Airtight IC Housing **New Construction**

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99ICA | Lamp: 50W MAX. |

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EL99A | Lamp: 50W MAX. |

| CAT NO. | SPECIFICATIONS |
|-----------|--------------------|
| EL99LDICA | Lamp: LED 12W MAX. |



4" Airtight IC Housing with GU24 Base Socket **New Construction**



4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| EL99ICA-G24 | Lamp: 18W MAX. |

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| EL99FICA | Lamp: 35W MAX. |

4" Accessories





Fire Enclosure



Mica Fire Tape

| CAT NO. | SPECIFICATIONS |
|---------|-------------------|
| FIRECVR | 9 ¾" H x 17" O.D. |

| CAT NO. | SPECIFICATIONS |
|------------|----------------------------|
| FIREENCL | 20 %" L x 14 %" W |
| FIREENCL-S | Shallow, 16" L x 14 $\%$ " |

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| FIRETAPE | ³⁄4″ W × 16′ L |