

Project name:	
Fixture type:	
Date:	

4" Reflector with Wall Wash Trim



Features

- Wall Wash with White Scoop.
- Lamp: 32W MAX CFL (PL-T) or 50W PAR20, R20.
- O.D.: 4 3/4".

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options







Clear w/White Trim Gold w/White Trim

All White

Product Numbers

Item	Description	Finish
EL925C		Clear with White Trim
EL925G		Gold with White Trim
EL925W		All White
EL925KC	with Socket Bracket	Clear with White Trim
EL925KW	with Socket Bracket	All White

Product Number Builder Example: EL925C

4" Wall Wash Trim White Scoop Socket Bracket Finish

no Socket Bracket

K Socket Bracket

Clear with White Trim

G Gold with White Trim

W All White

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing New Construction




4" Airtight IC Housing New Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket New Construction

	-			
FA.		-273D		
PIG.	100	=	-	

4" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL99ICA-G24	Lamp: 18W MAX.	

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories



Fire Cover

Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow. 16" L x 14 3%" \

CAT NO.	SPECIFICATIONS
FIRETAPE	³ ⁄ ₄ " W × 16' L