

Project name:

Fixture type:

Date:

# 4" Remodel Housing with Adjustable Lampholder



### Features

- 4" Remodel Housing.
- Integral thermal protector guards against improper lamping.
- Four remodel clips secure housing and accommodate various ceiling thickness.
- Adjustable socket bracket allows for different lamp types/sizes and proper and consistent lamp positioning.
- Pre-wired junction box provided with 1/2" and 3/4" knockouts and with removable access plates.
- Trims sold separately.
- Lamp: 50W MAX.
- Can be retrofitted to use 120V MR16 lamps with PSA28 adapter.
- cUL Listed for damp location and for feed through.

# **Technical Details**

#### Construction:

- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
  Aluminum housing for greater heat dissipation.
- Installation: Designed for ceiling plenums where 2x6 joists or taller are used. Maximum hole cutout is 4
- 1/4". See installation sheet for detailed information.

#### Electrical:

- Input Voltage: 120V AC.
- Thermally protected against improper lamping.

Trims: Compatible with ELCO 4" Line Voltage PAR trims.

Lamp: Designed for use with Medium Base (E26) PAR lamps up to 50W.

#### Listings:


- cUL Listed for Damp Location.
- cUL Listed for Feed Through.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

**Warranty:** ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.

# Specifications

| Wattage              | 50W               |  |  |  |
|----------------------|-------------------|--|--|--|
| Voltage              | 120V              |  |  |  |
| Lamp Type            | Medium Base (E26) |  |  |  |
| Damp Location Listed |                   |  |  |  |
|                      |                   |  |  |  |

# Dimensions



## **Product Numbers**

| Item   | Description  | Lamp type         | Watts | Voltage |
|--------|--------------|-------------------|-------|---------|
| EL99RA | Non-Airtight | Medium Base (E26) | 50W   | 120V    |