

| Project name: | |
|---------------|--|
| Fixture type: | |
| Date: | |

4" Remodel Housing with Adjustable Lampholder




Features

- 4" Remodel Housing.
- Integral thermal protector guards against improper lamping.
- Four remodel clips secure housing and accommodate various ceiling thickness.
- Adjustable socket bracket allows for different lamp types/sizes and proper and consistent lamp positioning.
- Pre-wired junction box provided with 1/2" and 3/4" knockouts and with removable access plates.
- Trims sold separately.
- Lamp: 50W MAX.
- Can be retrofitted to use 120V MR16 lamps with PSA28 adapter.
- cUL Listed for damp location and for feed through.

Specifications

| Wattage | 50W | | | |
|----------------------|-------------------|--|--|--|
| Voltage | 120V | | | |
| Lamp Type | Medium Base (E26) | | | |
| Damp Location Listed | | | | |

Dimensions



Product Number

| Item | Description | Lamp type | Watts | Voltage |
|--------|--------------|-------------------|-------|---------|
| EL99RA | Non-Airtight | Medium Base (E26) | 50W | 120V |

Technical Details

Construction:

- $\bullet\,$ Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- · Aluminum housing for greater heat dissipation.

Installation: Designed for ceiling plenums where 2x6 joists or taller are used. Maximum hole cutout is 41/4". See installation sheet for detailed information.

Electrical

- Input Voltage: 120V AC.
- Thermally protected against improper lamping.

Trims: Compatible with ELCO 4" Line Voltage PAR trims.

Lamp: Designed for use with Medium Base (E26) PAR lamps up to 50W.

Listings:

- · cUL Listed for Damp Location.
- · cUL Listed for Feed Through.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.