

4" Remodel IC Airtight Housing for 2-Hr Fire Rated Ceilings



Maximum 2-Hour Fire Rated ceiling assembly can be maintained when installed according to the International Building Code, Section 714.


Features

- Remodel IC Airtight Housing for 2-Hour Fire Rated ceilings
- Round opening for easy hole cutting
- Maximum 2-Hour Fire Rated ceiling assembly can be maintained when installed according to the International Building Code, Section 714
- Covered by U.S. Patents
- **NOTE:** Remodel tabs will not be completely covered by trims, painting may be required after installation or use of Oversized Ring (ELJ40V) to cover tabs

Specifications

Voltage	120V
Dimmable	Triac/ELV

Front View



Technical Details

Installation: Remodel tabs for easy installation. See installation sheet for detailed information


Mounting: Pre-installed remodel clips for easy installation.

Dimmability: Dimmability based on lamp.

Listings: IC Rated for direct contact with insulation. For 2-Hr Fire Rated ceilings. cUL listed under cUL 514A Standards as a metallic outlet box

Compatible With: Koto™ Fixtures, LED Disk Lights, LED Sky™ Panels, and LED Ceiling Mount Fixtures

Bottom View



Product Number


Item	Description	Voltage	Dimming
EJB4RICA	4" O.D. x 4 1/2" H	120V	Triac/ELV

Compatible Products



For use with Housings for 2-Hour Fire Rated Ceilings

Koto™ LED Module



Koto™ LED Module
ELK07, ELK09, & ELK11

PRODUCT NUMBER BUILDER			
Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
07	750 lm	27 2700K	(blank) 38° lens (Standard)
09	950 lm	30 3000K	-S 18° lens
11	1150 lm	35 3500K	-N 25° lens
		40 4000K	-W 60° lens
		SD Sunset Dimming (For ELK09 & ELK11)	-FC 18° - 50° Adjustable (ELK07 Only)

ACCESSORIES



Lens

- EP731C** 18° Lens
- EP732C** 25° Lens
- EP733C** 38° Lens
- EP734C** 60° Lens

*EP732C, EP733C, EP734C Included




Shoot

- L50W** White
- L50B** Black



Secondary Optics

- L45** Hex Louver (Black)
- L57** Hex Louver (White)
- L46** Linear Lens
- L47** Spread Louver
- L49** Frosted Lens
- L51** Color Shifter
- L52** Blue Optic Lens
- L53** Pink Optic Lens



Koto™ LED Module with 5-CCT Switch




10° Koto™ LED Module (Narrow Spot)

- Product** ELK08CT5 825 lm
- Number:** ELK10CT5 1000 lm

- Product** ELK0827-NSP 825 lm, 2700K
- Number:** ELK0830-NSP 1000 lm, 3000K

4" Pex™ Twist-On Trims



Adjustable Gimbal

ELK4129

Finishes:

(W, BB, BZ, B, C, H)




Adjustable Pinhole

ELK4127

Finishes:

(W, BB, BZ, B, H, CP)




Shallow Reflector

ELK4116

Finishes:

(W, H)




Adjustable Gimbal

ELK4229

Finishes:

(W, BB, BZ, B, C, H)




Adjustable Pinhole

ELK4227

Finishes:

(W, BB, BZ, B, N)



Shallow Reflector

ELK4216

Finishes:

(W, H)

4" Unique™ Twist-On Trims




Shallow Reflector

ELK4710

Finishes:

(W, B, BZ)



Shallow Baffle

ELK4713

Finishes:

(W, BZ)



Wall Wash

ELK4715

Finishes:

(W, BZ)




Adjustable Spot

ELK4188

Finishes:

(W, B, BZ)




Square Reflector

ELK4714

Finishes:

(W, B, BZ)



Square Baffle

ELK4716

Finishes:

(W, BZ)


4" Flush Mount Trim Adaptors



Round Adaptor

EL4FMR

- For use with ALO™ New Construction Box only (ELJ444)
- Compatible with ELK4116, ELK4127, ELK4129, ELK4710, ELK4713, ELK4715



Square Adaptor

EL4FMS


- For use with ALO™ New Construction Box only (ELJ444)
- Compatible with ELK4216, ELK4227, ELK4229,

*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring

Compatible Products

For use with **Housings for 2-Hour Fire Rated Ceilings**

4" LED Inserts




Round 5-CCT LED Reflector

CAT NO.	SPECIFICATIONS
EL455CT5W	12W, 850 lm, 2700K - 5000K



Round Reflector

CAT NO.	SPECIFICATIONS
EL41527W	10W, 800 lm, 2700K
EL41530W	10W, 850 lm, 3000K
EL41535W	10W, 900 lm, 3500K
EL41540W	10W, 900 lm, 4000K
EL41550W	10W, 950 lm, 5000K
EL415CT5W, BZ	12W, 850 lm, 2700K - 5000K



High Lumen Round Reflector


CAT NO.	SPECIFICATIONS
EL41727C, H	14W, 1000 lm, 2700K
EL41730W, C	14W, 1000 lm, 3000K
EL41735W, C, H	14W, 1100 lm, 3500K
EL41740W, C, H	14W, 1200 lm, 4000K
EL417CT5W, H	14W, 1000 lm 2700K - 5000K



Sunset Dimming Reflector/Baffle

CAT NO.	SPECIFICATIONS
EL415SDW, BZ	10W, 700 lm, Sunset, Reflector
EL410SDW, BZ	10W, 700 lm, Sunset, Baffle

- Dims from 3000K to 1800K on standard dimmer
- Not for use with Housings with Emergency Backup (EM)



Round Baffle

CAT NO.	SPECIFICATIONS
EL41027W	10W, 800 lm, 2700K
EL41030W	10W, 850 lm, 3000K
EL41035W	10W, 900 lm, 3500K
EL41040W	10W, 900 lm, 4000K
EL410CT5W, BB	12W, 850 lm, 2700K - 5000K



High Lumen Round Baffle

CAT NO.	SPECIFICATIONS
EL412CT5W	14W, 1000 lm, 2700K - 5000K



Round CCT Adjustable Gimbal

CAT NO.	SPECIFICATIONS
EL416CT3W	9W, 700 lm, 2700K - 3500K
EL416CT5B, BZ	9W, 700 lm, 2700K - 5000K



Square CCT Adjustable Gimbal

CAT NO.	SPECIFICATIONS
EL446CT3W	9W, 700 lm, 2700K - 3500K
EL446CT5B, BZ	9W, 700 lm, 2700K - 5000K



Square CCT Baffle

CAT NO.	SPECIFICATIONS
EL441CT3W, BZ	10W, 750 lm, 2700K - 3500K


*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **H** - Haze/White Ring, **C** - Chrome/White Ring

Compatible Products




For use with **Housings for 2-Hour Fire Rated Ceilings**

4" LED Inserts



Square Reflector

CAT NO.	SPECIFICATIONS
EL442CT3W, BB, BZ	11W, 790 lm, 2700K - 3500K



Round Baffle Gimbal


CAT NO.	SPECIFICATIONS
EL414CT5W, B	12W, 675 lm, 2700K - 5000K



Round 0-10V Reflector

CAT NO.	SPECIFICATIONS
EL49530DW	12W, 800 lm, 3000K, 120/277V

Accessories



Hard Wire Adapter

CAT NO.	SPECIFICATIONS
PSA38	Hard wire adapter with push-in connector to male quick connect terminal



Hard Wire Adapter

CAT NO.	SPECIFICATIONS
PSA38-4	Wire adapter to male quick connect terminal



Hard Wire Adapter (for EL49530DW)

CAT NO.	SPECIFICATIONS
P436-PG	Hard wire adapter with push-in connector to male 0-10V dimming wires. For use with EL49530DW Round 0-10V LED Insert only



Remodel Box Oversize Ring

CAT NO.	SPECIFICATIONS
ELJ40V	Recommended to use with EJB4RICA only, to cover tabs

*Finishes: **W** - All White, **B** - All Black, **BZ** - All Bronze

Compatible Products



For use with **Housings for 2-Hour Fire Rated Ceilings**

4" LED Disk Lights



4" Round Alva™ Disk Light


CAT NO.	SPECIFICATIONS
ELSF4030BZ, N	13W, 800 lm, 3000K
ELSF40CT5W	10.5W, 700 lm, 2700K-5000K



6" Round Alva™ Disk Light


CAT NO.	SPECIFICATIONS
ELSF1127W	13W, 900 lm, 2700K
ELSF11CT5W, BZ	15W, 900 lm, 2700K-5000K

Round & Square LED Sky Panels™



Round LED Sky Panel™

CAT NO.	SPECIFICATIONS
ELSP43CT5W	4", 10W, 600 lm, 2700K - 5000K
ELSP63CT5W, B	6", 15W, 900 lm, 2700K - 5000K
ELSP63DXCT3W, B	6", 14W, 1000 lm, 3000K-4000K, 0-10V dimmable
ELSP8327W, B	8", 18W, 1150 lm, 2700K
ELSP83CT3W, B	8", 18W, 1200 lm, 3000K - 4000K
ELSP83DXCT3W, B	8", 17W, 1400 lm, 3000K-4000K, 0-10V dimmable
ELSP12CT5W, B	12", 22W, 1450 lm, 2700K - 5000K



Square LED Sky Panel™


CAT NO.	SPECIFICATIONS
ELSP4430W	4", 10W, 600 lm, 3000K
ELSP4440W, B	4", 10W, 650 lm, 4000K
ELSP66CT5W, B	6", 15W, 900 lm, 2700K - 5000K
ELSP8830B	8", 18W, 1200 lm, 3000K
ELSP8840W, B	8", 18W, 1300 lm, 4000K
ELSP2240B	12", 22W, 2160 lm, 4000K
ELSP22CT5W	12", 22W, 1450 lm, 2700K - 5000K

XL LED Sky Panel™



CAT NO.	SPECIFICATIONS
ELSP1224CT5W	12" x 24", 22W, 2000 lm, 3000K - 5000K
ELSP1248CT3W	12" x 48", 40W, 4000 lm, 3000K, 4000K, 5000K
ELSP2424CT3W	24" x 24", 40W, 4000 lm, 3000K, 4000K, 5000K
ELSP2448CT3W	24" x 48", 40W, 4000 lm, 3000K, 4000K, 5000K

Accessories for LED Sky Panels™



Emergency Battery Back-Up


CAT NO.	SPECIFICATIONS
KEM-ELSW	15W, 900 lm, 120V, For use with 4" & 6" Sky Panels™ only

*Finishes: **W** - All White, **B** - All Black, **BZ** - All Bronze, **N** - All Nickel

Compatible Products


For use with **Housings for 2-Hour Fire Rated Ceilings**

Ceiling Mount LED Fixtures



Darby™ Standard LED Fixtures

CAT NO.	SPECIFICATIONS
ELD11030W, B	10", 14W, 980 lm, 3000K
ELD11040W, B	10", 14W, 1010 lm, 4000K
ELD14CT5W, B	14", 25W, 1700 lm, 2700K - 5000K
ELD11630W, B	16", 26W, 1820 lm, 3000K
ELD11640W, B	16", 26W, 1930 lm, 4000K



HIGH LUMEN

Darby™ High Lumen LED Fixtures

CAT NO.	SPECIFICATIONS
ELD21030W, B, BZ	10", 18W, 1170 lm, 3000K
ELD21040W, B, BZ	10", 18W, 1260 lm, 4000K
ELD21430W, B, BZ	14", 26W, 1690 lm, 3000K
ELD21440W, B, BZ	14", 26W, 1820 lm, 4000K
ELD21630W, B, BZ	16", 30W, 1950 lm, 3000K
ELD21640W, B, BZ	16", 30W, 2100 lm, 4000K



Dustin™ Standard LED Fixtures

CAT NO.	SPECIFICATIONS
ELD31230W	12", 14W, 980 lm, 3000K
ELD31240W	12", 14W, 980 lm, 4000K
ELD31430W	14", 18W, 1260 lm, 3000K
ELD31440W	14", 18W, 1260 lm, 4000K



HIGH LUMEN

Dustin™ High Lumen LED Fixtures

CAT NO.	SPECIFICATIONS
ELD32230W	12", 22W, 1540 lm, 3000K
ELD32240W	12", 22W, 1540 lm, 4000K
ELD32430W	14", 26W, 1820 lm, 3000K
ELD32440W	14", 26W, 1820 lm, 4000K
ELD32630W	16", 30W, 2100 lm, 3000K
ELD32640W	16", 30W, 2100 lm, 4000K

*Finishes: **W** - All White, **B** - All Black, **BZ** - All Bronze, **N** - All Nickel