

# 4" Shallow Remodel Housing

4" shallow remodel housing featuring a socket for use with 120V GU10 MR16 LED lamps.



## Features

- Single wall IC construction, for use in insulated ceilings.
- Lamp: 120V, 12W MAX MR16 GU10 LED (not included).
- Lamp Holder: GU10 MR16.
- Trims sold separately.

## Specifications

<b>Wattage</b>	12W
<b>Voltage</b>	120V
<b>Lamp Type</b>	GU10
<b>Wet Location</b>	Listed with Shower Trims
<b>Damp Location</b>	Listed

## Technical Details

### Construction:

- Single wall IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/4" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

**Installation:** Designed for ceiling plenums where 2x6 joists or taller joists are used. Maximum hole cutout is 4 1/4". Remodel clips secure housing, suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

**Electrical:** Input Voltage: 120V AC. Thermally protected against improper lamping.

**Trims:** Compatible with ELCO 4" MR16 Trims: EL2488, EL2440, EL2443, EL1488, EL1433, EL2482, EL2483, EL2484, EL1415 EL1421.


**Dimmability:** Dimmability based on lamp.

**Lamp:** Designed for use with GU10 MR16 LED lamps.

### Listings:

- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2016-E lamp/luminaire for Title 24 Compliance.

**Warranty:** ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 3 years.




## Product Numbers

Item	Lamp type	Watts	Voltage
EL49LDRICAS	GU10	12W	120V

# Compatible Products

For use with 4" IC Airtight GU10 Housings

## 4" MR16 Trims



**Clear Reflector Shower Trim with Frosted Glass Pinhole**

CAT NO.	SPECIFICATIONS
EL1415W	White
EL1415B	Black
EL1415G	Gold
EL1415N	Nickel
EL1415BZ	Bronze
EL1415SH	Lexan




**Gimbal Ring Baffle Trim (25°)**

CAT NO.	SPECIFICATIONS
EL1433W	All White
EL1433B	White/Black Ring




**Die-Cast Adjustable Spot Trim (0-30°)**

CAT NO.	SPECIFICATIONS
EL1488W	All White
EL1488B	All Black
EL1488BZ	All Bronze




**Square Adjustable Gimbal Baffle Trim (25°)**

CAT NO.	SPECIFICATIONS
EL2440W	All White
EL2440B	All Black
EL2440BZ	All Bronze




**Square Adjustable Gimbal Trim (25°)**

CAT NO.	SPECIFICATIONS
EL2443W	All White
EL2443B	All Black




**Steel Construction Square Adjustable Reflector Trim**

CAT NO.	SPECIFICATIONS
EL2482W	All White
EL2482CN	Clear/White Ring



**Die-Cast Aluminum Square Adjustable Baffle Trim**

CAT NO.	SPECIFICATIONS
EL2484W	All White
EL2484B	All Black
EL2484BZ	All Bronze



**Die-Cast Adjustable with Square Trim**

CAT NO.	SPECIFICATIONS
EL2488W	All White
EL2488B	All Black
EL2488BZ	All Bronze



**Adjustable Reflector Trim (25°)**


CAT NO.	SPECIFICATIONS
EL1421W	All White
EL1421WN	White/Nickel Ring
EL1421WBZ	White/Bronze Ring
EL1421B	Black/White Ring
EL1421BB	All Black
EL1421BN	Black/Nickel Ring
EL1421BZ	All Bronze
EL1421C	Chrome/White Ring
EL1421CN	Chrome/Nickel Ring
EL1421H	Haze/White Ring
EL1421DC	Clear/White Ring

## Accessories



**Fire Cover**

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



**Fire Enclosure**

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



**Mica Fire Tape**

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L