

Project name:		
Fixture type:		
Date:		

## 4" Shower Trim with Frosted Lens



#### **Features**

- Shower Trim with Frosted Lens.
- Lamp: 32W MAX CFL (PL-T) or 30W MAX R20.
- O.D.: 4 3/4".

#### **Technical Details**

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



# ItemFinishEL912BAll BlackEL912BZAll BronzeEL912SHWhite LexanEL912NNickel

**Product Numbers** 

EL912W

#### Product Number Builder Example: EL912B

4" Shower Trim with Frosted Lens	Finish
EL912	
	B All Black
	BZ All Bronze

N NickelW All White

SH White Lexan

### **Compatible** Products



For use with 4" Trims for PAR Lamps

#### 4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction** 



4" Airtight Housing **New Construction** 



4" Airtight IC Housing **New Construction** 

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction** 



4" Airtight IC 2-Hour Fire Rated Housing **New Construction** 

CAT NO.	SPECIFICATIONS	
FI 99ICA-G24	Lamp: 18W MAX.	

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

#### 4" Accessories

CAT NO.

**FIRECVR** 



Fire Cover

SPECIFICATIONS

9 3/4" H x 17" O.D.

K 4

Fire Enclosure



CAT NO.	SPECIFICATIONS
FIREENCL	20 %" L x 14 %" W
FIREENCL-S	Shallow, 16" L x 14 %" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS	
FIRETAPE	<sup>3</sup> ⁄ <sub>4</sub> " W × 16' L	