

# 4" Shower Trim with Reflector and Drop Opal Lens



## Features

- Shower Trim with Reflector and Drop Opal Lens.
- Lamp: 26W max CFL (PL-T), 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

## Technical Details

**Construction:** Meticulously manufactured trim with a powder coated or anodized finish.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 4" Line Voltage IC and Non-IC versions.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Options



**Bronze**



**White**



**White Lexan**



**Black**

## Product Numbers

Item	Finish
EL9116BZ	All Bronze
EL9116SH	White Lexan
EL9116W	All White
EL9116B	All Black

## Product Number Builder Example: EL9116BZ

4" Shower Trim with Reflector and Drop Opal Lens

Finish

**EL9116**

- BZ** All Bronze
- SH** White Lexan
- W** All White
- B** All Black

# Compatible Products

For use with 4" Trims for PAR Lamps

## 4" Line Voltage ICA Housings



4" Airtight IC Housing  
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket  
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

## 4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L