

Project name:		
Fixture type:		
Date:		

4" Shower Trim with Reflector and Fresnel Lens



Features

- Shower Trim with Reflector and Fresnel Lens.
- Lamp: 32W max CFL (PL-T), 40W MAX A19, 50W PAR20.
- O.D.: 4 3/4"

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

White Bronze White Lexan

Product Numbers

Options

Item	Finish	
EL9113BZ	All Bronze	
EL9113SH	White Lexan	
EL9113W	All White	

Product Number Builder Example: EL9113BZ

4" Shower Trim with Reflector and Fresnel Lens

Finish

EL9113

BZ All Bronze

SH White Lexan

W All White

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**



4" Airtight IC Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction**



4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories

CAT NO.

FIRECVR



Fire Cover

SPECIFICATIONS

9 3/4" H x 17" O.D.





Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 %" L x 14 %" W
FIREENCL-S	Shallow, 16" L x 14 %" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L