

4" Smooth Reflector Trim



Features

- Smooth Reflector Trim.
- Includes field changeable 3-optic lens (14°, 24°, 36°).
- O.D.: 4 7/8".

Specifications

Beam Angle 14°, 24°, 36°

Technical Details

Construction:

- Meticulously manufactured trim with powder coated or anodized finish.
- Diecast trim ring for durability and lasting quality.

Installation: Clips securely mount trim into housing and keeps ring flush with ceiling.

Housings: Compatible with ELD46ICA, ELDR46ICA.

Options



Haze w/White Trim Black w/White Trim All White


Product Numbers

Item	Beam Angle	Finish
EL4499W	14°, 24°, 36°	All White
EL4499B	14°, 24°, 36°	Black with White Trim
EL4499H	14°, 24°, 36°	Haze with White Trim

Compatible Products




4" Integrated LED Housings



IC Airtight New Construction Housing

CAT NO.	SPECIFICATIONS
ELD47ICA	1200 lm/ 16W / 2700K
ELD46ICA	1200 lm/ 16W / 3000K
ELD45ICA	1200 lm/ 16W / 4000K



IC Airtight Remodel Housing

CAT NO.	SPECIFICATIONS
ELDR47ICA	1200 lm/ 16W / 2700K
ELDR46ICA	1200 lm/ 16W / 3000K
ELD45ICA	1200 lm/ 16W / 4000K